

SSM-S Stainless Steel Corner Mirrors



Mirror Model	Reflective Area (Y)	Mounting Height (L1)	Mirror Height (L2)*	Data Sheet
SSM-100-S	100 mm	211 mm	178 mm	67200
SSM-150-S	150 mm	261 mm	228 mm	
SSM-200-S	200 mm	311 mm	278 mm	
SSM-250-S	250 mm	361 mm	328 mm	
SSM-375-S	375 mm	486 mm	453 mm	
SSM-475-S	475 mm	586 mm	553 mm	
SSM-550-S	550 mm	661 mm	628 mm	
SSM-675-S	675 mm	786 mm	753 mm	
SSM-825-S	825 mm	936 mm	903 mm	
SSM-875-S	875 mm	986 mm	953 mm	
SSM-975-S	975 mm	1086 mm	1053 mm	
SSM-1100-S	1100 mm	1211 mm	1178 mm	
SSM-1175-S	1175 mm	1286 mm	1253 mm	
SSM-1275-S	1275 mm	1386 mm	1353 mm	
SSM-1400-S	1400 mm	1511 mm	1478 mm	
SSM-1475-S	1475 mm	1586 mm	1553 mm	
SSM-1550-S	1550 mm	1661 mm	1628 mm	
SSM-1675-S	1675 mm	1786 mm	1753 mm	
SSM-1750-S	1750 mm	1861 mm	1828 mm	
SSM-1900-S	1900 mm	2011 mm	1978 mm	

* The mounting brackets may be inverted from the positions shown (flanges pointing "inward" instead of "outward," as shown). When this is done, dimension L2 decreases by 58 mm.

** One EZA-MBK-2 adapter bracket kit required if used with a MSA stand.

NOTE: The total range decreases by approximately 30% per mirror.

CABLES & WIRING

BRACKETS

CORNER MIRRORS

STANDS

HARSH DUTY SOLUTIONS

REPLACEMENT PARTS

ACCESSORIES