





SMB18UR	SMB22A	SMB3018SC	SMB30A			
						
All measurements in mm	All measurements in mm	All measurements in mm	All measurements in mm			
Hole center spacing: A = 25.4, B = 46.7 Hole size: A, B = 6.9 x 32, C = ø 18.3	Hole center spacing: A to B = 26 Hole size: A = ø 4.6, B = 4.6 x 16.9, C = 22.2	Hole center spacing: A = 50.8 Hole size: A = ø 7, B = ø 18	Hole center spacing: A to B = 40 Hole size: A = ø 6.3, B = 27.1 x 6.3, C = ø 30.5			
<ul style="list-style-type: none"> 2-piece universal swivel bracket 300 series stainless steel Stainless steel swivel locking hardware included Mounting hole for 18 mm sensor 	<ul style="list-style-type: none"> Right-angle bracket with curved slot for versatile orientation 12-ga. stainless steel Mounting hole for 22 mm sensor 	<ul style="list-style-type: none"> 18 mm swivel side or barrel-mount bracket Black reinforced thermoplastic polyester Stainless steel swivel locking hardware included 	<ul style="list-style-type: none"> Right-angle bracket with curved slot for versatile orientation Clearance for M6 (1/4") hardware Mounting hole for 30 mm sensor 12-ga. stainless steel 			
Barrel Mount	Base Mount	Barrel Mount	Barrel Mount			
						
Used with	Used with	Used with	Used with			
QS18* MINI-BEAM S18 M18 T18 TM18 S18U	QS18U* Q45UR S18C2 Q45UR M18C2 T18U EZ-LIGHT T18 EZ-LIGHT M18	K30L	M18/S18/T18 S18U Q45UR S18C2	Q45UR M18C2 T18U EZ-LIGHT T18	QS30 SM30/SMI30 S30 T30	T30U EZ-LIGHT T30 PICO-GUARD Point
Base Mount			Side Mount	Base Mount		
						
Used with			Used with			
Q25			QS18 MINI-BEAM QS18U	QM42/QMT42 QS18U	Q40 Q45 OMNI-BEAM OTB/LTB VTB STB Q45U	Q45UR QT50U QT50R K50 EZ-LIGHT K50L EZ-LIGHT TL50 EZ-LIGHT CL50 WL50 Work Lights
* Contact factory to verify compatibility with integral QD models.			Used with	Used with		
				Q25		

More on next page