









SMBAMSRAB	SMBARP..30	SMBASCM	SMBBSSM								
 <p>All measurements in mm</p> <p>Hole center spacing: A to B = 12 B to C = 11, A to C = 23, A to D = 55, E to E = 50.8 Hole size: A, B, C, D = 6.9 x 32, E = 6.9 x 89.4</p>	 <p>All measurements in mm</p> <p>Hole center spacing: A = 69.9 Hole size: A = ø 12.8</p>	 <p>All measurements in mm</p> <p>Hole center spacing: A = 25.4, A to B = 12.7 Hole size: A = ø 5 (M16), B = ø 5 (1/4-20)</p>	 <p>All measurements in mm</p> <p>Hole center spacing: A = 167.8 Hole size: A = ø 5.5</p>								
<ul style="list-style-type: none"><li>• 10-ga. (3.4 mm) cold-rolled steel with zinc finish</li><li>• Retrofit WORLD-BEAM QS30 in place of MULTI-BEAM, MAXI-BEAM, Q45, OMNI-BEAM and VALU-BEAM sensors</li></ul>	<table><tr><th>Model</th><th>Rope Pull</th></tr><tr><td>SMBARPL30</td><td>Left</td></tr><tr><td>SMBARPR30</td><td>Right</td></tr><tr><td>SMBARPB30</td><td>Both</td></tr></table>	Model	Rope Pull	SMBARPL30	Left	SMBARPR30	Right	SMBARPB30	Both	<ul style="list-style-type: none"><li>• Column-mount bracket</li><li>• 316 stainless steel</li><li>• Stainless steel hardware included</li></ul>	<ul style="list-style-type: none"><li>• Surface-mount bracket</li><li>• 316 stainless steel</li><li>• Stainless steel hardware included</li><li>• Set of two brackets</li></ul>
Model	Rope Pull										
SMBARPL30	Left										
SMBARPR30	Right										
SMBARPB30	Both										
Barrel Mount	Base Mount	Back Mount	Back Mount								
 <p>Used with</p> <p>QS30*</p>	 <p>Used with</p> <p>K50</p>	 <p>Used with</p> <p>Sealed Area Light (70 mm)</p>	 <p>Used with</p> <p>Backlights (75 x 150 mm) Backlights (150 x 150 mm) Backlights (150 x 225 mm) Backlights (150 x 300 mm) WLA Work Lights</p>								
* Requires a SMBAMS30RA bracket (sold separately)		NOTE: Shown with optional SMBPPK6 mounting kit (see page 724).									

More on next page