









SMBQS30YL	SMBR55F01	SMBR55F02	SMBR55FRA
 <p>All measurements in mm</p>	 <p>All measurements in mm</p>	 <p>All measurements in mm</p>	 <p>All measurements in mm</p>
<p>Hole size: A = <math>\varnothing</math> 15.3</p>	<p>Hole center spacing: A, B, C = 50.8, A to B, B to C = 25.3 Hole size: A, C = <math>\varnothing</math> 5.6, B = 11 x 5</p>	<p>Hole center spacing: A = 50.3 Hole size: A = 11.2 x 5.6</p>	<p>Hole center spacing: A = 20 Hole size: A = <math>\varnothing</math> 5.4</p>
<ul style="list-style-type: none"> <li>• Heavy-duty die-cast bracket designed for industrial protection</li> <li>• Replaceable window</li> <li>• M18 vertical mount option</li> <li>• Includes nuts and lock washer</li> </ul>	<ul style="list-style-type: none"> <li>• Flat-mounting bracket</li> <li>• Eliminates need for DIN rail</li> <li>• Molded PBT polyester</li> <li>• Black reinforced thermoplastic polyester</li> </ul>	<ul style="list-style-type: none"> <li>• Mounts to T-slotted or narrow flat surfaces</li> <li>• 19-ga. stainless steel</li> </ul>	<ul style="list-style-type: none"> <li>• Side-mounting bracket</li> <li>• Eliminates need for DIN rail</li> <li>• 19-ga. stainless steel</li> </ul>
Side Mount	Back Mount	Back Mount	Side Mount
 <p>Used with</p>	 <p>Used with</p>	 <p>Used with</p>	 <p>Used with</p>
QS30 (DC only)	R55F D10 D12 PICO-GUARD SFA-RD	PICO-GUARD SFA-RD	R55F D10 D12 PICO-GUARD SFA-RD

More on next page