

### 3-Pin Mini-Style Cable

**Cable:** PVC jacket, polyurethane connector body, nylon coupling nut  
**Conductors:** 18 AWG high-flex stranded, PVC insulation, gold-plated contacts  
**Temperature:** -40° to +80° C  
**Voltage Rating:** 250V ac/300V dc



Pinout	Model	Style	Length	Dimensions	Used With
<p>1 = Green/Yellow 2 = Brown 3 = Blue</p>	QDS-315C	Female Straight	5 m		<ul style="list-style-type: none"> <li>EZ-SCREEN Emitters w/3-pin QD (Point &amp; Grid)</li> </ul>
	QDS-325C		8 m		
	QDS-350C		15 m		
	QDS-375C		23 m		
	QDS-3100C		30 m		

### 4-Pin Mini-Style Cables

**Cable:** PVC jacket, polyurethane connector body, nylon coupling nut  
**Conductors:** 18 AWG high-flex stranded, PVC insulation, gold-plated contacts  
**Temperature:** -40° to +80° C  
**Voltage Rating:** 250V ac/300V dc



Pinout	Model	Style	Length	Dimensions	Used With
<p>1 = Brown 2 = White 3 = Blue 4 = Black</p>	MBCC-406	Female Straight	2 m		<ul style="list-style-type: none"> <li>STB w/solid-state relay</li> <li>OTB w/solid-state relay</li> </ul>
	MBCC-412		4 m		
	MBCC-430		9 m		

### 5-Pin Mini-Style Cables with Yellow Wire

**Cable:** PVC jacket, polyurethane connector body, nylon coupling nut  
**Conductors:** 18 AWG high-flex stranded, PVC insulation, gold-plated contacts  
**Temperature:** -40° to +80° C  
**Voltage Rating:** 250V ac/300V dc



Pinout	Model	Style	Length	Dimensions	Used With
<p>1 = Black 2 = Blue 3 = Yellow 4 = Brown 5 = White</p>	MBCC-506	Female Straight	2 m		<ul style="list-style-type: none"> <li>STB w/em relay</li> <li>OTB w/em relay</li> </ul>
	MBCC-512		4 m		
	MBCC-530		9 m		

CABLES & WIRING

BRACKETS

CORNER MIRRORS

STANDS

HARSH DUTY SOLUTIONS

REPLACEMENT PARTS

ACCESSORIES