

## 5-Pin Mini-Style Cordsets with Shield and "Twisted Pair"

**Cable:** PVC jacket, PUR (polyurethane) connector body, nickel-plated brass coupling nut

**Conductors:** 20 AWG (shielded), PVC insulation, gold-plated contacts

**Voltage Rating:** 250V ac/300V dc

**Temperature:** -40° to +90° C      **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Straight	4.57 m	QDC-515C	7.00 mm		<p><b>Female</b></p> <p>1 = Black 2 = Blue 3 = Drain 4 = Brown 5 = White</p>	<ul style="list-style-type: none"> <li>• MINI-ARRAY</li> <li>• High-Resolution MINI-ARRAY</li> </ul>
	7.62 m	QDC-525C				
	15.2 m	QDC-550C				
	22.9 m	MAQDC-575C				
	30.5 m	MAQDC-5100C				
	38.1 m	MAQDC-5125C				
45.7 m	MAQDC-5150C					

## 8-Pin Mini-Style Cordsets

**Cable:** PVC jacket, PUR (polyurethane) connector body, nylon coupling nut

**Conductors:** 20 AWG, PVC insulation, gold-plated contacts

**Voltage Rating:** 250V ac/300V dc

**Temperature:** -40° to +80° C      **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Straight	4.51 m	QDS-815C	6.90 mm		<p><b>Female</b></p> <p>1 = Brown      5 = Black 2 = Or/Bk      6 = Blue 3 = Orange    7 = Gn/Ye 4 = White      8 = Violet</p>	<ul style="list-style-type: none"> <li>• EZ-SCREEN Receivers w/8-pin QD (Point &amp; Grid)</li> <li>• DUO-TOUCH SG Run Bar</li> </ul>
	7.62 m	QDS-825C				
	15.2 m	QDS-850C				
	22.9 m	QDS-875C				

## BNC Coaxial Video Cordsets

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Video Coaxial with BNC	1.83 m	BNC06	6.00 mm		<p><b>Male</b></p>	<ul style="list-style-type: none"> <li>• Pro</li> <li>• P4</li> </ul>
	4.57 m	BNC15				
	9.14 m	BNC30				
	14.6 m	BNC48				

## BNC to 4-Pin Threaded M8/Pico-Style Cordsets with Shield

**Cable:** PVC jacket, PUR (polyurethane) connector body, nickel-plated brass coupling nut on QD end  
**Conductors:** 26 AWG  
**Voltage/Current Rating:** 125V ac/125V dc, 4.0 A  
**Temperature:** -40° to +105° C      **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
BNC/ Pico QD Straight	2.00 m	PKG4M-2/CS	4.40 mm		<p><b>Female</b></p> <p>1 = Brown      3 = Blue 2 = Not Used    4 = Drain</p> <p><b>Male</b></p>	• IP68 Sealed P4
	5.00 m	PKG4M-5/CS				
	9.00 m	PKG4M-9/CS				

Accessories

Brackets

Cordsets

Retroreflectors

Miscellaneous

Reference

## Communication Cordsets

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
5-Pin M12/ Euro-Style, Straight	1.83 m	MQDMC-506	5.60 mm		<p><b>Male</b></p> <p>1 = Brown 2 = White 3 = Blue 4 = Black 5 = Gray</p>	• EZ-ARRAY to INTUSB485-1 USB Serial Adapter
	4.57 m	MQDMC-515				
	9.14 m	MQDMC-530				
5-Pin M12/ Euro-Style, Right-Angle	1.83 m	MQDMC-506RA	5.60 mm		<p><b>Male</b></p> <p>1 = Brown 2 = White 3 = Blue 4 = Black 5 = Gray</p>	• EZ-ARRAY to INTUSB485-1 USB Serial Adapter
	4.57 m	MQDMC-515RA				
	9.14 m	MQDMC-530RA				