

3-Pin Threaded M8/Pico-Style Cordsets

Cable: PVC jacket, PUR (polyurethane) connector body, nickel-plated brass coupling nut
Conductors: 24 AWG, gold-plated contacts
Voltage/Current Rating: 125V ac/dc, 4.0 A
Temperature: -40° to +105° C **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Straight	2.00 m	PKG3M-2	4.40 mm		<p>Female</p> <p>1 = Brown 3 = Blue 4 = Black</p>	<ul style="list-style-type: none"> • Q12 • T8 • SB12 • VSM • VS1 • VS2 • VS3 • SLM • IP68 Sealed Ring Lights (nickel-plated) • On-Axis Lights
	5.00 m	PKG3M-5				
	7.00 m	PKG3M-7				
	9.00 m	PKG3M-9				
	10.0 m	PKG3M-10				
Right-Angle	2.00 m	PKW3M-2	4.40 mm		<p>Female</p> <p>1 = Brown 3 = Blue 4 = Black</p>	<ul style="list-style-type: none"> • IP68 Sealed Ring Lights (nickel-plated) • On-Axis Lights
	5.00 m	PKW3M-5				
	9.00 m	PKW3M-9				

3-Pin Threaded M8/Pico-Style Cordsets

Cable: PVC jacket and connector body, stainless steel coupling nut
Conductors: 24 AWG, gold-plated contacts
Voltage/Current Rating: 125V ac/dc, 4.0 A
Temperature: -40° to +90° C **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Straight	4.00 m	PKG3M-4	4.40 mm		<p>Female</p> <p>1 = Brown 3 = Blue 4 = Black</p>	<ul style="list-style-type: none"> • IP68 Sealed Ring Lights (stainless steel)
	7.00 m	PKG3M-7				
	10.0 m	PKG3M-10				

3-Pin Threaded/Snap M8/Pico-Style Cordsets – Double Ended

Cable: PVC jacket, PUR (polyurethane) connector body, nickel-plated brass (female) and nylon/nickel-plated brass (male) coupling nuts
Conductors: 24 AWG, gold-plated contacts
Voltage/Current Rating: 125V ac/dc, 4.0 A
Temperature: -40° to +105° C **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Straight	0.35 m	PKG3M-.35-PSG3M	4.40 mm		<p>Female</p> <p>1 = Brown 3 = Blue 4 = Black</p>	<ul style="list-style-type: none"> • IP68 Sealed P4 (connect IP68 Sealed Ring Light to P4)
	2.00 m	PKG3M-2-PSG3M				