

Eaton BSPMA2240S3GR

Catalog Number: BSPMA2240S3GR

Eaton Bussmann series BSPM series surge arrester, Technology type MOV, 230/400 Wye (4W+G), Surge arrester, Thermoplastic, UL94V14, 50/60 Hz, 200 Kilo Ampere, Thermoplastic, Remote Contact



General specifications

Product Name	Catalog Number
Eaton Bussmann series BSPM series surge arrester	BSPMA2240S3GR
	UPC
	051712709040
Product Length/Depth	Product Height
1.42 in	3.54 in
Product Width	Product Weight
2.56 in	0.52 lb
Warranty	Compliances
Five year limited warranty	Contact factory
	RoHS Compliant
Certifications	
UL 94V0	
UL Listed	

defaultTaxonomyAttributeLabel

Type

Surge arrestor

Special features

Technology type MOV

Application

Surge Protection

Frequency rating

50/60 Hz

Nominal Discharge Current

20 kA

Operating voltage

600/1200

Voltage rating

230/400 Wye (4W+G)

Enclosure

Thermoplastic, UL94V14

Surge current

200 kA

Indicator type

Remote contact

Short-circuit rating

200 kA

Operating temperature

-35 to 85 °C

Mounting Method

35 mm DIN rail

Degree of protection

IP20

Material

Thermoplastic

Resources

Catalogs

[Bussmann series complete full line catalog no. 1007](#)

[BSPMA2240S3GR~240V Corner Gmd Delta, 2P](#)

Specifications and datasheets

[Eaton Specification Sheet - BSPMA2240S3GR](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)