

Eaton FRS-R-30

Catalog Number: FRS-R-30

Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 30 A, non-indicating fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc



General specifications

| | |
|----------------------------------|-----------------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series FRS-R fuse | FRS-R-30 |
| UPC | Product Length/Depth |
| 051712508346 | 11.63 in |
| Product Height | Product Width |
| 2.34 in | 2.34 in |
| Product Weight | Warranty |
| 2.25 lb | Not Applicable |
| Compliances | |
| CE Marked | |

Electrical rating

Amperage Rating

30 A

Interrupt rating

20 kAIC at 300 Vdc

200 kAIC at 600 Vac

Response time

10 sec at 500%

Voltage rating

600 Vac, 300 Vdc

Physical details

Number of elements

Dual

Packaging type

Standard

General information

Class

Class RK5

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Resources

Catalogs

[Bussmann Full Line Catalog](#)

[Low Voltage Branch Circuit Fuse Chapter](#)

Compliance information

[RoHS Search Tool](#)

Multimedia

[Bussmann series Fuseology](#)

Technical service bulletins

[Bussmann series FRS-R 600 V Class R up to 60 A fuse data sheet no.](#)

1017