



## N412 Double Door Wall-Mount Ultimate 30X42X10 Stainless Steel

By Wiegmann  
Catalog # [N412D304210SSC](#)



N412 Double Door Wall-Mount Ultimate 30X42X10 Stainless Steel

### Features

- Stainless steel construction
- Continuous welded seams
- Doors sealed with poured-in-place gaskets
- Grounding studs welded to doors and body
- Collar studs for mounting optional ULTIMATE series back panels
- 3-point keylocking/padlocking handle included
- NEMA 3R, 4, 4X, 12, 13 and IP66

### Application

Hubbell Wiegmann N412DSSC Ultimate Series Disconnects are designed to house and protect electrical and electronic components from harsh, dirty environments. For use in installations where dirt, dust, oil, water, or other contaminants are present.

### General

|                         |   |
|-------------------------|---|
| Catalog Number          | N412D304210SSC  |
| Color                   | Brushes Stainless Steel   |
| Construction            | Continuously Welded Seams   |
| Cover Type              | Door  |
| Finish Type             | Smooth Grained Stainless  |
| Knockouts               | No  |
| Latches Type            | 3-Point Handle  |
| Listings                | <ul style="list-style-type: none"><li>• cULus</li><li>• IEC 60529</li></ul> |
| Material                | Stainless Steel   |
| Mounting Type           | Mounting Holes  |
| Number of Doors (Fixed) | 2   |
| Number of Holes         | 4   |
| Series                  | Ultimate  |
| Sub Brand               | Ultimate Series   |
| Type                    | Enclosure   |
| UPC                     | 786725890514  |

### Dimensions

|                |             |
|----------------|-------------|
| Cubic Capacity | 12600 cu.in |
| Depth          | 10 in       |
| Height         | 30 in       |
| Width          | 42 in       |

### Conductor Related

|             |    |
|-------------|----|
| Cable Entry | NO |
|-------------|----|

### Certifications And Compliance

|                              |   |
|------------------------------|---|
| Buy American Compliant       | Contact Manufacturer  |
| Certification - CSA Approved | NO  |
| Certification - ETL          | NO  |
| Certification - cULus        | YES   |
| Certified Listed             | <ul style="list-style-type: none"><li>• cULus</li><li>• IEC</li></ul> |

|                      |   |
|----------------------|---|
| Industry Standard(s) | <ul style="list-style-type: none"><li>• cULus</li><li>• IEC</li><li>• cULus</li><li>• IEC 60529</li></ul> |
|----------------------|---|

|             |                 |
|-------------|-----------------|
| Nema Rating | 1,3R,12,13,4,4X |
|-------------|-----------------|

### Logistics

|                 |   |
|-----------------|---|
| Carton Quantity | 1 |
|-----------------|---|

### Product Assets

|  |
|--|
| <a href="#">3D Models - N412D304210SSC</a>   |
| <a href="#">Catalogs - Wiegmann Stainless Steel &amp; Aluminium</a>                      |
| <a href="#">Engineering Drawing - HWNDN412D304210SSC-S</a>                               |
| <a href="#">Sales Drawings - HWNDN412D304210SSC-S</a>                                    |
| <a href="#">SDS - HCC SDS</a>  |
| <a href="#">Sell Sheets - N412 ULTIMATE Stainless Steel Series Double Door Enclosure</a> |
| <a href="#">Specifications - N412D304210SSC</a>  |
| <a href="#">Terms and Conditions - HCC Terms &amp; Conditions</a>                        |



A Hubbell brand