

15A; 20A 2-P 3-W

LEVITON®

10 YEAR LIMITED
WARRANTY

ELECTRICAL		
DIELECTRIC VOLTAGE	CURRENT INTERRU.	TEMP. RISE
Withstands 2000V per UL 498	Full rated current	Max 30°C after 250 cycles of overload at 200% of rated current

MECHANICAL			
TERMINAL I.D.	TERMINAL ACCOMM.	PRODUCT I.D.	CORD GRIP RANGE
Brass, hot Grounding White, neutral	#12 – #18 AWG	Ratings & NEMA I.D. permanently marked on device	.240" – .655"
ENVIRONMENTAL			
FLAMMABILITY		OPERATING TEMP.	
Rated V-2 per UL 94		-40°C to 60°C	

STANDARDS & CERTIFICATIONS					
NEMA WD-6	ANSI C-73	UL 498	UL Fed Spec Listed WC-596	CSA C22.2 No. 42	NOM
✓	✓	✓	#E13393	#LR-406	#057



Dustguard Products
Are Engineered to Meet
or Exceed UL and IEC
Dust-tight Standards



1447



1449



1433



2447




1549




1533

TYPE	PLUG	NEMA PLUG	CONNECTOR	NEMA CONNECTOR
15A 125V, 2-P 3-W Straight Blade, Grounding				
Yellow EPTR	1447	 5-15P	1547	 5-15R
15A 250V, 2-P 3-W Straight Blade, Grounding				
Yellow EPTR	1449	 6-15P	1549	 6-15R
20A 125V, 2-P 3-W Straight Blade, Grounding				
Yellow EPTR	1433	 5-20P	1533	 5-20R
20A 250V, 2-P 3-W Straight Blade, Grounding				
Yellow EPTR	1448	 6-20P	1548	 6-20R
15A 125V, 2-P 3-W Locking, Grounding				
Yellow EPTR	2447	 L5-15P	2547	 L5-15R



PLUG



CONNECTOR

To learn more about Leviton devices or for answers to technical questions call our Techline at 1-800-824-3005 or visit us at www.leviton.com

Courtesy of Steven Engineering, Inc.-230 Ryan Way, South San Francisco, CA 94080-6370-Main Office: (650) 588-9200-Outside Local Area: (800) 258-9200-www.stevenengineering.com