



15A 125V

LEVITON®

Industrial Grade Back & Side Wired, Self Grounding



NEMA 5-15R



NEMA L5-15R

LIFETIME WARRANTY

| ELECTRICAL | | |
|-----------------------------|--------------------|--|
| DIELECTRIC VOLTAGE | CURRENT INTERR. | TEMP. RISE |
| Withstands 2000V per UL 498 | Full rated current | Max 30°C after 250 cycles of overload at 200% of rated current |

| MECHANICAL | | | |
|---|------------------|--|-----------------|
| TERMINAL I.D. | TERMINAL ACCOMM. | PRODUCT I.D. | CORD GRIP RANGE |
| Brass, hot Grounding White, neutral | #18 - #10 AWG | Ratings & NEMA I.D. permanently marked on device | - |
| ENVIRONMENTAL | | | |
| FLAMMABILITY | | OPERATING TEMP. | |
| Rated V-2 per UL 94 | | -40°C to 60°C | |

| STANDARDS & CERTIFICATIONS | | | | | |
|----------------------------|-----------|---------|---------------------------|-----------------|------|
| NEMA WD-6 | ANSI C-73 | UL 498 | UL Fed Spec Listed WC-596 | CSA C22.2 No.42 | NOM |
| ✓ | ✓ | #E13399 | #E13399 | #152105 | #057 |




4702-IIR




4792

| FACE COLOR | COMBINATION LOCKING DUPLEX RECEPTACLE | NEMA CONFIGURATIONS | FEEDS |
|--------------------------------|---------------------------------------|---------------------|--|
| 15A 125V, 2-P 3-W, NEMA L5-15R | | | |
| Black | 4700 | | Common Feed |
| Black | 4702-IIR | | 2 Hot, 1 Neutral Return |
| Black | 4703-IIR | | Split Feed 2 Hot, 2 Neutral Returns |

| FACE COLOR | COMBINATION LOCKING & STRAIGHT BLADE DUPLEX RECEPTACLE | NEMA CONFIGURATIONS | FEEDS |
|---|--|---------------------|--|
| 15A 125V, 2-P 3-W, NEMA L5-15R & NEMA 5-15R | | | |
| Black | 4792 | | Common Feed |
| Black | 4794-1R | | 2 Hot, 1 Neutral Return |
| Black | 4795-2R | | Split Feed 2 Hot, 2 Neutral Returns |



4702 & 4703



4792, 4794, 4795

Industrial Grade Combination Locking & Straight Blade Receptacles

