



LIFETIME WARRANTY



NEMA L6-15P



NEMA L6-15R

Industrial Grade

ELECTRICAL		
DIELECTRIC VOLTAGE	CURRENT INTERR.	TEMP. RISE
Withstands 2000V per UL 498	Full rated current	Max 30°C after 250 cycles of overload at 200% of rated current

MECHANICAL			
TERMINAL I.D.	TERMINAL ACCOMM.	PRODUCT I.D.	CORD GRIP RANGE
Brass, hot	#18 – #10 AWG	Ratings & NEMA I.D. permanently marked on device	.245" – .700"
Grounding			
White, neutral			
ENVIRONMENTAL			
FLAMMABILITY		OPERATING TEMP.	
Rated V-2 per UL 94		-40°C to 60°C	

STANDARDS & CERTIFICATIONS					
NEMA WD-6	ANSI C-73	UL 498	UL Fed Spec Listed WC-596	CSA C22.2 No.42	NOM
✓	✓	✓	#E13393 Plugs, Connectors & Flanged Inlets	#LR-406	#057
			#E13399 Receptacles & Flanged Outlets		



4550 (DUPLEX)




4570-CY



4579-CY



4570-CA



4586-C



TYPE	PLUG	CONNECTOR	ANGLE PLUG	FLANGED INLET	FLANGED OUTLET
15A 250V, NEMA L6-15P AND L6-15R, 2-P 3-W, Grounding					
All Black — Bulk Packaged	4570-B	4579-B	—	—	—
Black & White	4570-C	4579-C	4570-CA	—	—
Yellow & White	4570-CY	4579-CY	—	—	—
All White	—	—	—	4586-C	4585-C
Power Indication Black & White	4570-PLC	4579-PLC	—	—	—

TYPE	DUPLEX RECEPTACLE SELF-GROUNDING	DUPLEX RECEPTACLE ISOLATED GROUND	SINGLE RECEPTACLE	SINGLE RECEPTACLE with SHORT STRAP	SINGLE RECEPTACLE ISOLATED GROUND
15A 250V, NEMA L6-15R, 2-P 3-W, Grounding					
Black	4550	—	4560	4560-SS	—
Orange	—	4550-IG	—	—	4560-IG

THERMOPLASTIC ELASTOMER BOOTS		GRAY LEXAN FLIP LID COVER	302 STAINLESS STEEL	302 STAINLESS STEEL
For Plugs	For Connectors	For Inlets and Outlets	Single Receptacles	Duplex Receptacles
<p>6017-L (Black) 6017-LY (Yellow)</p>	<p>6018-L (Black) 6018-LY (Yellow)</p>	<p>IP64 Rated Includes Gasket WP1</p>	<p>1.40" Dia. Hole 84004-40</p>	<p>84003-40</p>
FOR DIMENSIONS SEE PAGE E42			FOR ADDITIONAL WALLPLATE OPTIONS SEE SECTION Q	

