

500 SERIES MEDICAL EQUIPMENT FOR HAZARDOUS LOCATIONS

CLASS I, DIVISION 1, Group C & D

CLASS I, ZONE 1, Group IIA & IIB

NEMA Type 7C

EN 60529 Degree of Protection IP41

Nonsparking cast aluminum housing. Aluminum base plate with nonskid conductive rubber base pad. Both models prewired with potted connector MS-3102R-18-4PW. Two pedal model wired with an electrical interlock and supplied with a divider bar between pedals which helps prevent accidental operation of both pedals at one time. Foot switch painted black.

Use mating connector MS-3106A-18-4SW, plus strain relief clamp MS-3057-10 or 10A*

*Mating connector with cable clamp available from LINEMASTER. Order as Catalog Number LSC-835.

Size: 10" x 9 3/4" x 4 3/8"

Weight: 6 1/2 lbs.



SINGLE PEDAL

600 SERIES MEDICAL EQUIPMENT FOR HAZARDOUS LOCATIONS

CLASS I, DIVISION 1, Group C & D

CLASS I, ZONE 1, Group IIA & IIB

NEMA Type 7C


EN 60529 Degree of Protection IP68

Meets IEC 601-2-2

Medical Explosion Proof foot switch Series 600 is a UL Listed construction that allows the addition of sealing O-rings on the pivot rod and between the base and cover. This is accomplished by increasing the thickness of the housing wall, without negating the integrity of the metal to metal contact required to qualify as explosion proof. The same specifications apply for the 600 Series as detailed above for the 500 Series, except for a modest increase in weight and the mating connector required. Use mating connector MS or CA-3106F-18-4SW-(A105)-(F74)* which includes cable clamp, or CA-06R-18-4SW-(A105)-(F74)* which includes cable clamp.

*Mating connector with cable clamp available from LINEMASTER. Order as Catalog Number LSC-575-24.

▲ WARNING SEE INSIDE FRONT COVER



TWO PEDAL

SPECIFICATIONS (Special variations are available to the O.E.M. on special order on the models listed below)


CATALOG NUMBER	CIRCUIT	FORM	CONNECTOR WIRED	ELECTRICAL RATINGS
UL _{us} C E 591-EX (Single Pedal)	SPDT	C	Pin A-Normally Open	
UL _{us} C E 601-EX (Single Pedal)	SPDT	C	B-Common	
			C-Normally Closed	5 A 125-250 VAC
			D-Ground	3 A 28 VDC
UL _{us} C E 596-EX (Two Pedal)	SPNO	A	Pin A-Normally Open-Left Pedal	Momentary Contact
UL _{us} C E 606-EX (Two Pedal)	Both Sides	A	B-Common	
			C-Normally Open-Right Pedal	
			D-Ground	

CE MARKING – see note on inside front cover.


Industrial Explosion Proof Models

NOTE: DIMENSIONS ARE FOR REFERENCE ONLY

500 Series




600 Series



Medical Explosion Proof Models

NOTE: DIMENSIONS ARE FOR REFERENCE ONLY

500 Series



600 Series

