



DSN60 RECEPTACLE

63-64047-972-375-843-NC

SPECIFICATIONS

60A

277/480 VAC

Type 4X & IP69

5 hp/20 hp

Rated Current (A)	60A
Rated Voltage (V)	277/480 VAC
Horsepower Rating	5 hp/20 hp
Contact Configuration	3P+N+G
Auxiliary Contacts	+2 AUX
Ratings Information	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
Environmental Rating	Type 4X IP 66/67 IP 69
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK08
Material	POLY
Product Color	BLUE
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	14 AWG - 4 AWG SCREW TERMINAL
Applicable Standards	UL 1682 UL 2682 cCSAus C22.2 No. 182.1-13
Option(1)	PADLOCKABLE MUSHROOM PAWL
Option(2)	NORMALLY CLOSED LID
Accessory Size	3
Base Drawing Number	63-64xxx.pdf
Catalog	meltric-catalog-dsn60-en.pdf