

A.  
System  
Overview

B1.  
Cable Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions


F.  
Index



## Pan-Ty® Clamp Ties – Nylon 6.6

- For indoor use
- Used to secure a cable bundle to another surface such as a control panel, communication rack, wall or ceiling
- Design allows for bundling before or after screwing clamp in place

- One-piece construction for consistent performance and reliability
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation
- UL Listed for use in plenum or air handling spaces per NEC



| Part Number | Length |    | Width |    | Thickness |    | Nominal Hole Dia. |    | Screw Size | Metric Screw Size | Max. Bundle Dia. |    | Min. Loop Tensile Str. |   | Recommended Installation Tool | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|--------|----|-------|----|-----------|----|-------------------|----|------------|-------------------|------------------|----|------------------------|---|-------------------------------|----------------|----------------|
|             | In.    | mm | In.   | mm | In.       | mm | In.               | mm |            |                   | In.              | mm | Lbs.                   | N |                               |                |                |

### Miniature Cross Section – Plenum-Rated

|                   |     |     |      |     |      |     |      |     |    |      |     |    |    |    |                                  |     |      |
|-------------------|-----|-----|------|-----|------|-----|------|-----|----|------|-----|----|----|----|----------------------------------|-----|------|
| <b>PLC1M-S4-C</b> | 4.3 | 109 | .100 | 2.5 | .045 | 1.1 | .122 | 3.1 | #4 | M2.5 | .75 | 19 | 18 | 80 | GTS, GTSL, GS2B, PTS, PPTS, STS2 | 100 | 1000 |
|-------------------|-----|-----|------|-----|------|-----|------|-----|----|------|-----|----|----|----|----------------------------------|-----|------|

### Intermediate Cross Section – Plenum-Rated

|                     |     |     |      |     |      |     |      |     |    |    |      |    |    |     |                                  |     |      |
|---------------------|-----|-----|------|-----|------|-----|------|-----|----|----|------|----|----|-----|----------------------------------|-----|------|
| <b>PLC1.5I-S8-C</b> | 6.1 | 155 | .135 | 3.4 | .045 | 1.1 | .174 | 4.4 | #8 | M4 | 1.25 | 32 | 40 | 178 | GTS, GTSL, GS2B, PTS, PPTS, STS2 | 100 | 1000 |
|---------------------|-----|-----|------|-----|------|-----|------|-----|----|----|------|----|----|-----|----------------------------------|-----|------|

### Standard Cross Section – Plenum-Rated

|                    |      |     |      |     |      |     |      |     |     |    |      |     |    |     |                                                        |     |      |
|--------------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|----|-----|--------------------------------------------------------|-----|------|
| <b>PLC2S-S6-C</b>  | 7.9  | 201 | .190 | 4.8 | .047 | 1.2 | .148 | 3.8 | #6  | M3 | 1.84 | 47  | 50 | 222 | GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2 | 100 | 1000 |
| <b>PLC2S-S10-C</b> | 7.9  | 201 | .190 | 4.8 | .047 | 1.2 | .200 | 5.1 | #10 | M5 | 1.84 | 47  | 50 | 222 |                                                        | 100 | 1000 |
| <b>PLC3S-S10-C</b> | 12.0 | 305 | .190 | 4.8 | .047 | 1.2 | .200 | 5.1 | #10 | M5 | 3.00 | 76  | 50 | 222 |                                                        | 100 | 1000 |
| <b>PLC4S-S10-C</b> | 15.0 | 381 | .190 | 4.8 | .052 | 1.3 | .200 | 5.1 | #10 | M5 | 4.00 | 102 | 50 | 222 |                                                        | 100 | 1000 |


### Light-Heavy Cross Section – Plenum-Rated

|                    |      |     |      |     |      |     |      |     |     |    |      |     |     |     |                                    |    |     |
|--------------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|-----|-----|------------------------------------|----|-----|
| <b>PLC2H-S25-L</b> | 9.0  | 229 | .300 | 7.6 | .075 | 1.9 | .260 | 6.6 | 1/4 | M6 | 2.00 | 51  | 120 | 534 | GTH, GS4H, GS4EH, PTH, STH2, ST3EH | 50 | 500 |
| <b>PLC4H-S25-L</b> | 15.1 | 384 | .300 | 7.6 | .075 | 1.9 | .260 | 6.6 | 1/4 | M6 | 4.00 | 102 | 120 | 534 |                                    | 50 | 500 |

## Pan-Ty® Clamp Ties – Weather Resistant and Heat Stabilized Nylon 6.6

- Weather resistant material has greater resistance to damage caused by ultraviolet light – indoor or outdoor use
- Heat stabilized material for high temperature applications up to 239°F (115°C) – indoor use
- Used to secure a cable bundle to another surface such as a control panel, communication rack, wall or ceiling

- Design allows for bundling before or after screwing clamp in place
- One-piece construction for consistent performance and reliability
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation



| Part Number | Length |    | Width |    | Thickness |    | Nominal Hole Dia. |    | Screw Size | Metric Screw Size | Max. Bundle Dia. |    | Min. Loop Tensile Str. |   | Recommended Installation Tool | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|--------|----|-------|----|-----------|----|-------------------|----|------------|-------------------|------------------|----|------------------------|---|-------------------------------|----------------|----------------|
|             | In.    | mm | In.   | mm | In.       | mm | In.               | mm |            |                   | In.              | mm | Lbs.                   | N |                               |                |                |

### Weather Resistant Nylon 6.6

#### Miniature Cross Section

|             |     |     |      |     |      |     |      |     |    |      |     |    |    |    |                                  |     |      |
|-------------|-----|-----|------|-----|------|-----|------|-----|----|------|-----|----|----|----|----------------------------------|-----|------|
| PLC1M-S4-C0 | 4.3 | 109 | .100 | 2.5 | .045 | 1.1 | .122 | 3.1 | #4 | M2.5 | .75 | 19 | 18 | 80 | GTS, GTSL, GS2B, PTS, PPTS, STS2 | 100 | 1000 |
|-------------|-----|-----|------|-----|------|-----|------|-----|----|------|-----|----|----|----|----------------------------------|-----|------|

#### Intermediate Cross Section

|               |     |     |      |     |      |     |      |     |    |    |      |    |    |     |                                  |     |      |
|---------------|-----|-----|------|-----|------|-----|------|-----|----|----|------|----|----|-----|----------------------------------|-----|------|
| PLC1.5I-S8-C0 | 6.1 | 155 | .135 | 3.4 | .045 | 1.1 | .174 | 4.4 | #8 | M4 | 1.25 | 32 | 40 | 178 | GTS, GTSL, GS2B, PTS, PPTS, STS2 | 100 | 1000 |
|---------------|-----|-----|------|-----|------|-----|------|-----|----|----|------|----|----|-----|----------------------------------|-----|------|

#### Standard Cross Section

|              |      |     |      |     |      |     |      |     |     |    |      |     |    |     |                                                        |     |      |
|--------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|----|-----|--------------------------------------------------------|-----|------|
| PLC2S-S6-C0  | 7.9  | 201 | .190 | 4.8 | .047 | 1.2 | .148 | 3.8 | #6  | M3 | 1.84 | 47  | 50 | 222 | GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2 | 100 | 1000 |
| PLC2S-S10-C0 | 7.9  | 201 | .190 | 4.8 | .047 | 1.2 | .200 | 5.1 | #10 | M5 | 1.84 | 47  | 50 | 222 |                                                        | 100 | 1000 |
| PLC3S-S10-C0 | 12.0 | 305 | .190 | 4.8 | .052 | 1.3 | .200 | 5.1 | #10 | M5 | 3.00 | 76  | 50 | 222 |                                                        | 100 | 1000 |
| PLC4S-S10-C0 | 15.0 | 381 | .190 | 4.8 | .052 | 1.3 | .200 | 5.1 | #10 | M5 | 4.00 | 102 | 50 | 222 |                                                        | 100 | 1000 |

#### Light-Heavy Cross Section

|               |      |     |      |     |      |     |      |     |     |    |      |     |     |     |                                    |     |      |
|---------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|-----|-----|------------------------------------|-----|------|
| PLC2H-S25-TL0 | 9.0  | 229 | .300 | 7.6 | .075 | 1.9 | .260 | 6.6 | 1/4 | M6 | 2.00 | 51  | 120 | 534 | GTH, GS4H, GS4EH, PTH, STH2, ST3EH | 250 | 2500 |
| PLC4H-S25-L0  | 15.1 | 384 | .300 | 7.6 | .075 | 1.9 | .260 | 6.6 | 1/4 | M6 | 4.00 | 102 | 120 | 534 |                                    | 50  | 500  |

### Heat Stabilized Nylon 6.6

#### Miniature Cross Section

|              |     |     |      |     |      |     |      |     |    |      |     |    |    |    |                                  |      |       |
|--------------|-----|-----|------|-----|------|-----|------|-----|----|------|-----|----|----|----|----------------------------------|------|-------|
| PLC1M-S4-M30 | 4.3 | 109 | .100 | 2.5 | .045 | 1.1 | .122 | 3.1 | #4 | M2.5 | .75 | 19 | 18 | 80 | GTS, GTSL, GS2B, PTS, PPTS, STS2 | 1000 | 50000 |
|--------------|-----|-----|------|-----|------|-----|------|-----|----|------|-----|----|----|----|----------------------------------|------|-------|

#### Intermediate Cross Section

|                |     |     |      |     |      |     |      |     |    |    |      |    |    |     |                                  |      |       |
|----------------|-----|-----|------|-----|------|-----|------|-----|----|----|------|----|----|-----|----------------------------------|------|-------|
| PLC1.5I-S8-M30 | 6.1 | 155 | .135 | 3.4 | .045 | 1.1 | .174 | 4.4 | #8 | M4 | 1.25 | 32 | 40 | 178 | GTS, GTSL, GS2B, PTS, PPTS, STS2 | 1000 | 25000 |
|----------------|-----|-----|------|-----|------|-----|------|-----|----|----|------|----|----|-----|----------------------------------|------|-------|

#### Standard Cross Section

|               |      |     |      |     |      |     |      |     |     |    |      |     |    |     |                                                        |      |       |
|---------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|----|-----|--------------------------------------------------------|------|-------|
| PLC2S-S10-M30 | 7.9  | 201 | .190 | 4.8 | .047 | 1.2 | .200 | 5.1 | #10 | M5 | 1.84 | 47  | 50 | 222 | GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2 | 1000 | 10000 |
| PLC4S-S10-M30 | 15.0 | 381 | .190 | 4.8 | .052 | 1.3 | .200 | 5.1 | #10 | M5 | 4.00 | 102 | 50 | 222 |                                                        | 1000 | 5000  |

#### Light-Heavy Cross Section

|                |      |     |      |     |      |     |      |     |     |    |      |     |     |     |                                    |     |      |
|----------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|-----|-----|------------------------------------|-----|------|
| PLC2H-S25-TL30 | 9.0  | 229 | .300 | 7.6 | .075 | 1.9 | .260 | 6.6 | 1/4 | M6 | 2.00 | 51  | 120 | 534 | GTH, GS4H, GS4EH, PTH, STH2, ST3EH | 250 | 2500 |
| PLC4H-S25-TL30 | 15.1 | 384 | .300 | 7.6 | .075 | 1.9 | .260 | 6.6 | 1/4 | M6 | 4.00 | 102 | 120 | 534 |                                    | 250 | 2500 |

Note: UL Recognized and CSA Certified except PLC2H/4H in Weather Resistant material (0).

A.  
System  
Overview

B1.  
Cable  
Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index