

Short-circuit connector - KSS 3- 6 - 0309523

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Short-circuit connector, pitch: 6 mm, number of positions: 3, color: black

Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 001032 |
| GTIN | 4017918001032 |
| Weight per Piece (excluding packing) | 5.810 g |
| Custom tariff number | 85366990 |
| Country of origin | Poland |

Technical data

Technical data

| | |
|--|--------|
| Color | black |
| Material | Copper |
| Number of positions | 3 |
| Pitch | 6 mm |
| Flammability rating according to UL 94 | V2 |

Ambient conditions

| | |
|--|---|
| Operating temperature | -60 °C ... 105 °C (max. short-term operating temperature 125°C) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Permissible humidity (storage/transport) | 30 % ... 70 % |
| Ambient temperature (assembly) | -5 °C ... 70 °C |

Short-circuit connector - KSS 3- 6 - 0309523

Technical data

Ambient conditions

| | |
|---------------------------------|-----------------|
| Ambient temperature (actuation) | -5 °C ... 70 °C |
|---------------------------------|-----------------|

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V2 |
|--|----|

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27141140 |
| eCl@ss 11.0 | 27141140 |
| eCl@ss 4.0 | 27060300 |
| eCl@ss 4.1 | 27060300 |
| eCl@ss 5.0 | 27141100 |
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27141100 |
| eCl@ss 7.0 | 27141140 |
| eCl@ss 9.0 | 27141140 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000448 |
| ETIM 6.0 | EC000489 |
| ETIM 7.0 | EC000489 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11 | 31251501 |
| UNSPSC 12.01 | 31251501 |
| UNSPSC 13.2 | 39121426 |
| UNSPSC 18.0 | 39121426 |
| UNSPSC 19.0 | 39121426 |

Short-circuit connector - KSS 3- 6 - 0309523

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 20.0 | 39121426 |
| UNSPSC 21.0 | 39121426 |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|--------------------------|
| EAC |  | RU C- DE.BL08.B.00511 |
|-----|---|--------------------------|
