

Touch panel - BTP 2102W - 1046667

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 25.9 cm / 10.2" TFT-display (analog resistive (polyester)), 800 x 480 pixel(s) (WVGA), 262144 colors, Arm9™ i.MX28, 454 MHz, 2x COM (RS-232/422/485), 1x USB 2.0, Typ A, 1x USB 2.0, Typ B, 1 x Ethernet (10/100 Mbps), RJ45, Windows® CE 6.0 and user software: Visu+. (bus system: without)


Similar figure

Your advantages

- Visu+ RT integrated as standard in all BTP 2000 devices
- Connection to all relevant control systems, thanks to a large number of available drivers
- Developed for basic applications with attractive price/performance ratio
- 3 display sizes in 16:9 format



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 644103
GTIN	4055626644103
Weight per Piece (excluding packing)	1,200.000 g
Custom tariff number	84714100
Country of origin	India

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Outer dimensions: width, height, depth	268 mm x 190 mm x 5 mm (Dimensions of the front plate)
Installation dimensions: width, height, depth	256 mm x 178 mm x 33 mm (Installation cutout)

Touch panel - BTP 2102W - 1046667

Technical data

Display

Display type	25.9 cm / 10.2" TFT
Screen resolution	800 x 480 Pixel(s) (WVGA)
Touch technology	analog resistive (polyester)
Brightness	300 cd/m ² , typical (adjustable)
Backlighting	LED
Display backlight MTBF	20000 h
Colors	262144 colors
Reading angle left	65 °
Reading angle right	65 °
Reading angle top	45 °
Reading angle bottom	65 °

Computer data

Processor	Arm9™ i.MX28, 454 MHz
Operating system	Windows® CE 6.0
User software	Visu+
RAM	128 MB DDR2 SDRAM
Mass storage	Flash, 512 MB
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	2x COM (RS-232/422/485)
	1x USB 2.0, Typ A
	1x USB 2.0, Typ B
Bus system	without
Slots	1x SD

General

Housing material	Plastic
Mounting type	Front installation
Weight	900 g

Ambient conditions

Degree of protection	IP66 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Touch panel - BTP 2102W - 1046667

Technical data

Device supply

Typical current consumption	0.3 A
Power supply unit	24 V DC ±15 %

Standards and Regulations

Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Classifications

eCl@ss

eCl@ss 10.0.1	27330201
eCl@ss 11.0	27330201
eCl@ss 4.0	27330200
eCl@ss 4.1	27330200
eCl@ss 5.0	27330200
eCl@ss 5.1	27330200
eCl@ss 6.0	27242300
eCl@ss 7.0	27242302
eCl@ss 9.0	27330201

ETIM

ETIM 4.0	EC001412
ETIM 6.0	EC001412
ETIM 7.0	EC001412

Approvals

Approvals

Approvals

EAC-RoHS / EAC

Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approval details

Touch panel - BTP 2102W - 1046667

Approvals

EAC-RoHS		RU* DE*35.B.00394/20
----------	--	-------------------------

EAC		RU C- DE.A*08.B01708
-----	--	-------------------------

Accessories

Accessories

Data plug

D-SUB gender changer - VS-09-GC-ST/ST - 1652651



D-SUB contact insert, shell size 1, with nine signal contacts, type of contact pin, gender changer, fixing with 4-40 UNC thread

Operating stylus

Touch pen - TOUCH PEN - 2701379



Touch pen for analog-resistive HMIs, silver coated. Delivery includes self-adhesive pen holder.

PCB plug

Printed-circuit board connector - MSTB 2,5/ 3-ST-5,08 - 1757022



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Female connector, number of potentials: 3, Number of rows: 1, Number of positions per row: 3, number of connections: 3, product range: MSTB 2,5/..-ST, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, Locking clip: - Locking clip, plug-in system: CLASSIC COMBICON, Locking: without, mounting: without, type of packaging: packed in cardboard

Storage medium

Touch panel - BTP 2102W - 1046667

Accessories

USB memory stick - USB FLASH DRIVE - 2402809



USB memory stick, 8 GB

Memory - MICROSDHC-16GB - 1154696



Industrial grade 16 GB MicroSDHC 3DTLC

Memory - MICROSDHC-32GB - 1154699



Industrial grade 32 GB MicroSDHC 3DTLC
