

Software - VISU+ 2 RT-D 512 WEB2 - 1077278

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Runtime license for Visu+ including 2 web clients where the I/O data and variables in scripting are limited to 512 bytes. 2 direct driver connections are also supported.

Your advantages

- Full SCADA (Supervisory Control And Data Acquisition) function with visualization, trend representation, and alarm management
- Control coupling with OPC and 2 direct drivers
- Direct driver connection to controllers, e.g., to Siemens S7 or via Modbus/TCP and Modbus/RTU
- Data logging, trend display, and recipe management
- Scripts can be created in VBA and IL
- Fully scalable process diagrams for using one design on different devices and monitor sizes
- Multilingual software and projects, thanks to Unicode support and online selection
- Access protection with user management

VISU+
SCADA Visualization

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 790107
GTIN	4055626790107
Weight per Piece (excluding packing)	20.000 g
Custom tariff number	49119900
Country of origin	Germany

Technical data

License information

Intended use for the software	Visualization
Type of license	Runtime license

Functions

Basic functions	Know-How protection and safety through encoding of projects
-----------------	---

Software - VISU+ 2 RT-D 512 WEB2 - 1077278

Technical data

Functions

	Realtime database coupling with ODBC to MS ACCESS, MS EXCEL and SQL server
	FDA CFR 21 Part 11 compatible
Expanded functionality	Web client capability
Integrated function	Web client
	Online configuration
	Password protection
	Language selection
Number of I/O nodes	512 I/O bytes

Hardware requirements

Hard disk	min. 1 GByte (recommended: 2 GB)
RAM	min. 1 GByte (2 GB for Windows Vista and Windows 7)
CPU	Pentium/Celeron, 1.6 GHz
Optical drive	DVD-ROM
Screen resolution	rec. 1024 pixel(s) x 768 pixel(s) (XGA)

Software requirements

Languages supported	German, English, French, Italian
Supported browsers	Internet Explorer 5.5 or higher

Development environment requirements

Operating equipment	Keyboard, mouse
Operating system	Windows® 10
	Windows® 8.1
	Windows® 8
	Windows® 7
	Windows® Embedded Standard 7
	Windows® Server 2019
	Windows® Server 2016
	Windows® Server 2012 R2
	Windows® Server 2012
	Windows® Server 2008 R2
	Windows® Server 2008
	Windows® Server 2003
Note about the operating system	Server Core installations are not supported.

Runtime environment requirements

Software - VISU+ 2 RT-D 512 WEB2 - 1077278

Technical data

Runtime environment requirements

Operating system	Windows® 10
	Windows® 8.1
	Windows® 8
	Windows® 7
	Windows® Embedded Standard 7
	Windows® XP Embedded
	Windows® Server 2019
	Windows® Server 2016
	Windows® Server 2012 R2
	Windows® Server 2012
	Windows® Server 2008 R2
	Windows® Server 2008
	Windows® Server 2003
	Windows® CE 5.0
	Windows® CE 6.0
	Windows® Mobile

Classifications

eCl@ss

eCl@ss 10.0.1	27242502
eCl@ss 11.0	27242502
eCl@ss 4.0	27338000
eCl@ss 4.1	27338000
eCl@ss 5.0	27242500
eCl@ss 5.1	27242502
eCl@ss 6.0	27242500
eCl@ss 7.0	27242502
eCl@ss 9.0	27242502

ETIM

ETIM 4.0	EC001416
ETIM 6.0	EC001416
ETIM 7.0	EC001416

Software - VISU+ 2 RT-D 512 WEB2 - 1077278

Classifications

UNSPSC

UNSPSC 6.01	43163005
UNSPSC 7.0901	43232404
UNSPSC 11	43163005
UNSPSC 12.01	43232404
UNSPSC 13.2	43231507
UNSPSC 18.0	43231507
UNSPSC 19.0	43231507
UNSPSC 20.0	43231507
UNSPSC 21.0	43231507

Accessories

Accessories

Visualization

Software - VISU+ 2 - 2988544



Development license for Visu+ projects.