

Cable reel - SAC-3P-24AWG-OE-OE-544-100,0US - 1317476

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



By the meter, Cable reel, PVC, yellow, 3-wire, color single wire: brown, blue, black, cable length: 100 m



Key Commercial Data

Packing unit	1 pc
Country of origin	United States

Technical data

Dimensions

Length of cable	100 m
-----------------	-------

General

Number of positions	3
---------------------	---

Cable

Cable type	PVC gray 105 °C
Cable type (abbreviation)	544
UL AWM style	2517 (105 °C / 300 V)
AWG signal line	24
Core diameter including insulation	1.12 mm ±0.03 mm
Wire colors	brown, blue, black
Overall twist	3 wires, twisted
External cable diameter D	4.1 mm ±0.2 mm
Minimum bending radius, flexible installation	12 x D
Cable weight	21 kg/km
External sheath, color	yellow
Outer sheath, material	PVC
Material conductor insulation	PVC

Cable reel - SAC-3P-24AWG-OE-OE-544-100,0US - 1317476


Technical data

Cable

Conductor material	Tin-plated Cu litz wires
Insulation resistance	\geq (550 M Ohms/m @ 500V)
Conductor resistance	max. 79.7 Ω /km (20 °C)
Nominal voltage, cable	300 V
Other resistance	UV resistant
Flame resistance	FT4
Ambient temperature (operation)	-30 °C ... 105 °C (cable, fixed installation)

Drawings

Cable cross section



PVC gray 105 °C [544]

Cable reel - SAC-3P-24AWG-OE-OE-544-100,0US - 1317476

Classifications

eCl@ss

eCl@ss 11.0	27061801
-------------	----------

Accessories

Accessories

Stripping tool

Stripping tool - WIREFOX SAC - 1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length