

## Cable reel - SAC-3P-24AWG-OE-OE-535-300,0SH - 1422031


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



By the meter, Cable reel, shielded, PVC, black, 3-wire, color single wire: brown, blue, black, cable length: 300 m



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 0 5 5 6 2 6 3 2 4 9 6 8
GTIN	4055626324968
Custom tariff number	85444995
Country of origin	United States

### Technical data

#### Dimensions

Length of cable	300 m
-----------------	-------

#### General

Number of positions	3
---------------------	---

#### Cable

Cable type	Black PVC 105°C
Cable type (abbreviation)	535
UL AWM style	2517 (105 °C / 300 V)
AWG signal line	24
Conductor structure signal line	32x 1.10 mm
Core diameter including insulation	1.12 mm ±0.03 mm
Wire colors	brown, blue, black

## Cable reel - SAC-3P-24AWG-OE-OE-535-300,0SH - 1422031

### Technical data

#### Cable

Overall twist	3 wires, twisted
Shielding	Tinned copper braided shield
Optical shield covering	85 %
External sheath, color	black
External cable diameter D	4.7 mm ±0.2 mm
Minimum bending radius, flexible installation	12 x D
Cable weight	33 kg/km
Outer sheath, material	PVC
Material conductor insulation	PVC
Conductor material	Tin-plated Cu litz wires
Nominal voltage, cable	300 V
Other resistance	UV resistant
Flame resistance	FT4
Ambient temperature (operation)	-30 °C ... 105 °C (cable, fixed installation)


#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

### Drawings

# Cable reel - SAC-3P-24AWG-OE-OE-535-300,0SH - 1422031

Cable cross section



Black PVC 105°C [535]

## Classifications

eCl@ss

eCl@ss 10.0.1	27060106
eCl@ss 11.0	27061801
eCl@ss 5.1	27060300
eCl@ss 6.0	27060300
eCl@ss 7.0	27060307
eCl@ss 9.0	27062011

ETIM

ETIM 6.0	EC000830
----------	----------

# Cable reel - SAC-3P-24AWG-OE-OE-535-300,0SH - 1422031

## Classifications

### ETIM

ETIM 7.0	EC003249
----------	----------

### UNSPSC

UNSPSC 13.2	43211617
UNSPSC 19.0	43211617

## Accessories

### Accessories

#### Stripping tool

Stripping tool - WIREFOX SAC - 1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length