


## Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, shielded, Plug straight M8, on free cable end, cable length: 3 m

### Your advantages

- ✓ Easy and safe: 100% electrically tested plug-in components
- ✓ Our standard: robust halogen-free PUR cable
- ✓ Reliable signal transmission – 360° shielding in environments with electromagnetic interference



### Key Commercial Data

|                                      |               |
|--------------------------------------|---------------|
| Packing unit                         | 1 pc          |
| GTIN                                 |               |
| GTIN                                 | 4017918968809 |
| Weight per Piece (excluding packing) | 114.500 g     |
| Custom tariff number                 | 85444290      |
| Country of origin                    | Poland        |

### Technical data

#### Dimensions

|  |       |
|--|-------|
| Length of cable                            | 3 m   |
| Stripping length of the free conductor end | 50 mm |

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
|                                 | -25 °C ... 90 °C (Plug / socket) |
| Degree of protection            | IP65                             |

# Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821

## Technical data

### Ambient conditions

|  |      |
|--|------|
|  | IP67 |
|--|------|

### General

|                              |                              |
|------------------------------|------------------------------|
| Rated current at 40°C        | 4 A                          |
| Rated voltage                | 48 V AC                      |
|                              | 60 V DC                      |
| Number of positions          | 4                            |
| Insulation resistance        | ≥ 100 MΩ                     |
| Coding                       | A - standard                 |
| Standards/regulations        | M8 connector IEC 61076-2-104 |
| Status display               | No                           |
| Protective circuit/component | unwired                      |
| Overvoltage category         | II                           |
| Degree of pollution          | 3                            |
| Insertion/withdrawal cycles  | ≥ 100                        |
| Torque                       | 0.2 Nm (M8 connectors)       |

### Material

|  |   |
|--|---|
| Flammability rating according to UL 94 | HB  |
| Contact material                       | CuSn  |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Material, knurls                       | Zinc die-cast, nickel-plated                |

### Standards and Regulations

|  |                              |
|--|------------------------------|
| Standards/specifications               | M8 connector IEC 61076-2-104 |
| Flammability rating according to UL 94 | HB                           |

### Cable

|                                    |                                       |
|------------------------------------|---------------------------------------|
| Cable type                         | PUR halogen-free black                |
| Cable type (abbreviation)          | PUR                                   |
| Cable abbreviation                 | LiF9YC11Y                             |
| UL AWM style                       | 20549                                 |
| Conductor cross section            | 4x 0.25 mm <sup>2</sup> (Signal line) |
| AWG signal line                    | 24                                    |
| Conductor structure signal line    | 32x 0.10 mm                           |
| Core diameter including insulation | 1.17 mm ±0.02 mm (Signal line)        |
| Thickness, insulation              | ≥ 0.21 mm (Core insulation)           |

## Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821

### Technical data

#### Cable

|   |   |
|---|---|
|   | approx. 0.5 mm (Outer cable sheath)                                 |
| Wire colors                                   | brown, white, blue, black   |
| Overall twist                                 | 4 wires, twisted  |
| Shielding                                     | Braided copper wires  |
| Optical shield covering                       | 80 %  |
| External sheath, color                        | black-gray RAL 7021   |
| External cable diameter D                     | 4.7 mm ±0.15 mm   |
| Smallest bending radius, fixed installation   | 24 mm   |
| Smallest bending radius, movable installation | 48 mm   |
| Number of bending cycles                      | 10000000  |
| Bending radius                                | 48 mm   |
| Traversing path                               | 10 m  |
| Traversing rate                               | 3 m/s   |
| Acceleration                                  | 10 m/s <sup>2</sup>   |
| Cable weight                                  | 31 kg/km  |
| Outer sheath, material                        | PUR   |
| Material conductor insulation                 | PP  |
| Conductor material                            | Bare Cu litz wires  |
| Insulation resistance                         | ≥ 100 GΩ*km (at 20 °C)  |
| Conductor resistance                          | max. 78 Ω/km (at 20 °C)   |
| Nominal voltage, cable                        | ≤ 300 V   |
| Test voltage, cable                           | ≥ 3000 V  |
| Special properties                            | Flexible cable conduit capable                                      |
|   | Silicone-free   |
|   | Free of substances which would hinder coating with paint or varnish |
| Other resistance                              | Highly resistant to acids, alkaline solutions and solvents          |
|   | hydrolysis and microbe resistant                                    |
|   | partly UV-resistant in accordance with DIN EN ISO 4892-2-A          |
| Flame resistance                              | in accordance with UL 758/1581 FT2                                  |
|   | DIN EN 60332-2-2 (20 s)   |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815                            |
| Resistance to oil                             | in accordance with DIN EN 60811-2-1                                 |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)                        |
|   | -25 °C ... 80 °C (cable, flexible installation)                     |

#### Environmental Product Compliance

|            |  |
|------------|--|
| REACH SVHC | Lead 7439-92-1                                 |
| China RoHS | Environmentally Friendly Use Period = 50 years |

# Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821


## Technical data

### Environmental Product Compliance

|  |   |
|--|---|
|  | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |
|--|---|


## Drawings

Schematic diagram




Pin assignment M8 plug, 4-pos., view male side

Circuit diagram



Contact assignment of the M8 plug


Dimensional drawing



M8 x 1 male plug, straight version

# Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821

Cable cross section



PUR halogen-free black [PUR]

## Classifications

eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27060311 |
| eCl@ss 11.0   | 27060311 |
| eCl@ss 4.0    | 27060300 |
| eCl@ss 4.1    | 27060300 |
| eCl@ss 5.0    | 27061800 |
| eCl@ss 5.1    | 27061800 |
| eCl@ss 6.0    | 27279200 |
| eCl@ss 7.0    | 27279218 |
| eCl@ss 9.0    | 27060311 |

# Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000830 |
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 6.0 | EC001855 |
| ETIM 7.0 | EC001855 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 19.0   | 31251501 |
| UNSPSC 20.0   | 31251501 |
| UNSPSC 21.0   | 31251501 |

## Approvals


### Approvals

Approvals

UL Listed / cUL Listed / EAC-RoHS / EAC / cULus Listed

Ex Approvals

### Approval details

|                    |   |   |               |
|--------------------|---|---|---------------|
| UL Listed          |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 221474 |
| Nominal voltage UN | 30 V  |   |               |
| Nominal current IN | 4 A   |   |               |

# Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821

## Approvals

|                    |  |   |               |
|--------------------|--|---|---------------|
| cUL Listed         |  | <a href="http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm</a> | FILE E 221474 |
| Nominal voltage UN |  | 30 V  |               |
| Nominal current IN |  | 4 A   |               |

|          |  |                      |
|----------|--|----------------------|
| EAC-RoHS |  | RU D-DE.HB35.B.00387 |
|----------|--|----------------------|

|     |  |               |
|-----|--|---------------|
| EAC |  | EAC-Zulassung |
|-----|--|---------------|

|              |  |
|--------------|--|
| cULus Listed |  |
|--------------|--|

## Accessories

### Accessories

#### Conductor marking

Insert label - PABA WH/23 - 1013779



Insert label, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: thread on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

Insert label - PABA YE/23 - 1013782



Insert label, Strip, yellow, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: thread on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

#### Corrugated pipe

## Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821

### Accessories

Protective hose - WP-PA HF 13,0 BK - 3240681



Polyamide protective hose, inflammability class V0, UV resistant

---

Protective hose - WP-PA HF-HB 13,0 BK - 3240839



Polyamide protective hose, inflammability class HB, UV resistant

---

### Cutting tools

Diagonal cutter - CUTFOX-S VDE - 1212207



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

---

### Marker pen

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

---

### Protective cap

## Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821

### Accessories

Sealing cap - PROT-M 8 FS-PA-CHAIN - 1430857

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 plugs



---

### Screwdriver tools

Tool - SAC BIT M8-D10 - 1208461



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

---

### Stripping tool

Stripping tool - WIREFOX SAC-1 - 1212757



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from  $\varnothing$  of 3.2 to 4.4 mm, any stripping length

---

Stripping tool - WIREFOX SAC - 1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from  $\varnothing$  of 4.4 to 7 mm, any stripping length

---

Stripping tool - WIREFOX 10 - 1212150



Stripping tool, for cables and conductors from 0.02 - 10 mm<sup>2</sup>, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm<sup>2</sup> stranded/1.5 mm<sup>2</sup> solid, replaceable stripping blade

## Sensor/actuator cable - SAC-4P-M 8MS/ 3,0-PUR SH - 1521821

### Accessories

---

#### Torque tool

Torque screwdriver - TSD 02 SAC - 1208487



Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors

---

Protective hose adapter - WP-CTA POM 13,0 BK - 1422884



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

---