

Flush-type connector - SACC-E-M5MS-4CON-M5/0,5 - 1530595

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Flush-type connector, 4-position, Plug, straight, M5, Front mounting, M5 x 0.5, Individual wires, cable length: 0.5 m, 0.14 mm², TPE litz wire

Your advantages

- ✓ Pre-assembled with litz wires for immediate use
- ✓ Customer-specific assemblies and litz wire lengths available
- ✓ Sealed on the litz wire side for optimum leak-tightness



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 024396 |
| GTIN | 4046356024396 |
| Weight per Piece (excluding packing) | 9.300 g |
| Custom tariff number | 85444290 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|-----------------|-------|
| Length of cable | 0.5 m |
|-----------------|-------|

Ambient conditions

| | |
|---------------------------------|-------------------------|
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug) |
| | -25 °C ... 80 °C |
| Degree of protection | IP67 |

General

Flush-type connector - SACC-E-M5MS-4CON-M5/0,5 - 1530595

Technical data

General

| | |
|-----------------------|------------------------------|
| Rated current at 40°C | 1 A |
| Rated voltage | 48 V AC 60 V DC |
| Number of positions | 4 |
| Insulation resistance | ≥ 100 MΩ |
| Coding | A - standard |
| Standards/regulations | M5 connector IEC 61076-2-105 |
| Status display | No |
| Overvoltage category | II |
| Degree of pollution | 3 |
| Test voltage | 800 V |
| Connection method | Individual wires |
| Mounting type | Front mounting M5 x 0.5 |
| Thread type | M5 x 0.5 |

Material

| | |
|--|---------------------|
| Flammability rating according to UL 94 | HB |
| Contact material | CuZn |
| Contact surface material | Au |
| Contact carrier material | PA 6.6 |
| Material, knurls | Nickel-plated brass |
| Sealing material | Viton |

Cable

| | |
|---------------------------------|------------------------------|
| Cable type | TPE litz wire |
| Conductor cross section | 0.14 mm ² |
| AWG signal line | 26 |
| Conductor structure signal line | 18x 0.10 mm |
| Wire colors | brown, white, blue, black |
| Material conductor insulation | TPE |
| Standards/specifications | M5 connector IEC 61076-2-105 |
| Ambient temperature (operation) | -25 °C ... 80 °C |

Standards and Regulations

| | |
|--|------------------------------|
| Standards/specifications | M5 connector IEC 61076-2-105 |
| Flammability rating according to UL 94 | HB |

Environmental Product Compliance

| | |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

Flush-type connector - SACC-E-M5MS-4CON-M5/0,5 - 1530595


Technical data

Environmental Product Compliance


| | |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 25; |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Drawings

Dimensional drawing




Schematic diagram



Pin assignment M5 plug, 4-pos., view plug side

Dimensional drawing



M5 flush-type plug

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27440102 |
| eCl@ss 11.0 | 27440102 |
| eCl@ss 4.0 | 27140800 |
| eCl@ss 4.1 | 27140800 |
| eCl@ss 5.0 | 27143400 |
| eCl@ss 5.1 | 27143400 |
| eCl@ss 6.0 | 27279200 |
| eCl@ss 7.0 | 27440103 |
| eCl@ss 9.0 | 27440102 |

Flush-type connector - SACC-E-M5MS-4CON-M5/0,5 - 1530595

Classifications

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001297 |
| ETIM 3.0 | EC002061 |
| ETIM 4.0 | EC002062 |
| ETIM 6.0 | EC002061 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11 | 31251501 |
| UNSPSC 12.01 | 31251501 |
| UNSPSC 13.2 | 39121413 |
| UNSPSC 18.0 | 39121413 |
| UNSPSC 19.0 | 39121413 |
| UNSPSC 20.0 | 39121413 |
| UNSPSC 21.0 | 39121413 |

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|---------|
| EAC |  | B.01687 |
|-----|---|---------|

Accessories

Accessories

Flat nut

Flush-type connector - SACC-E-M5MS-4CON-M5/0,5 - 1530595

Accessories

Flat nut - SACC-E-MU-M 5 - 1535901



Flat nut with M5 thread

Phoenix Contact 2021 © - all rights reserved
<http://www.phoenixcontact.com>