


## PCB terminal block - MKDS 1/ 6-3,81 BK - 1800020

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Number of positions per row: 6, product range: MKDS 1, pitch: 3.81 mm, screw head form: L Slotted, color: black, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, type of packaging: packed in cardboard



### Key Commercial Data

|                                      |                                                                                                       |
|--------------------------------------|-------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                  |
| Minimum order quantity               | 50 pc                                                                                                 |
| GTIN                                 | <br>4 017918 961978 |
| GTIN                                 | 4017918961978                                                                                         |
| Weight per Piece (excluding packing) | 3.380 g                                                                                               |
| Custom tariff number                 | 85369010                                                                                              |
| Country of origin                    | Germany                                                                                               |

### Technical data

#### Item properties

|                       |                |
|-----------------------|----------------|
| Number of positions   | 6              |
| Drive form screw head | Slotted (L)    |
| Screw thread          | M2             |
| Pin layout            | Linear pinning |

#### Material data - housing

|               |              |
|---------------|--------------|
| Housing color | black (9005) |
|---------------|--------------|

#### Dimensions for the product

|                             |          |
|-----------------------------|----------|
| Length [ l ]                | 7.3 mm   |
| Width [ w ]                 | 22.85 mm |
| Height [ h ]                | 12 mm    |
| Pitch                       | 3.81 mm  |
| Height (without solder pin) | 8.5 mm   |
| Solder pin [P]              | 3.5 mm   |

# PCB terminal block - MKDS 1/ 6-3,81 BK - 1800020

## Technical data

### Dimensions for PCB design

|               |        |
|---------------|--------|
| Hole diameter | 1.1 mm |
|---------------|--------|

### Packaging information

|                            |                     |
|----------------------------|---------------------|
| Type of packaging          | packed in cardboard |
| Pieces per package         | 50                  |
| Denomination packing units | Pcs.                |

### Standards and Regulations

|                                  |        |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|                                  | CSA    |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | Environmentally Friendly Use Period = 50 years                                                      |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27440401 |
| eCl@ss 11.0   | 27460101 |
| eCl@ss 4.0    | 27141100 |
| eCl@ss 4.1    | 27141100 |
| eCl@ss 5.0    | 27141100 |
| eCl@ss 5.1    | 27261100 |
| eCl@ss 6.0    | 27261100 |
| eCl@ss 7.0    | 27440401 |
| eCl@ss 9.0    | 27440401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002643 |
| ETIM 6.0 | EC002643 |
| ETIM 7.0 | EC002643 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211801 |
| UNSPSC 7.0901 | 39121432 |
| UNSPSC 11     | 39121432 |
| UNSPSC 12.01  | 39121432 |

## PCB terminal block - MKDS 1/ 6-3,81 BK - 1800020

### Classifications

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 39121432 |
| UNSPSC 18.0 | 39121432 |
| UNSPSC 19.0 | 39121432 |
| UNSPSC 20.0 | 39121432 |
| UNSPSC 21.0 | 39121432 |

### Approvals

#### Approvals

#### Approvals

IECEE CB Scheme / SEV / EAC / cULus Recognized

#### Ex Approvals

#### Approval details

|                    |                                                                                     |                                                           |          |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|----------|
| IECEE CB Scheme    |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | CH-10787 |
| Nominal voltage UN | 160 V                                                                               |                                                           |          |
| Nominal current IN | 12 A                                                                                |                                                           |          |
| mm²/AWG/kcmil      | 1.5                                                                                 |                                                           |          |

|                    |                                                                                     |                                                                       |         |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------|---------|
| SEV                |  | <a href="https://www.eurofins.ch/de/">https://www.eurofins.ch/de/</a> | IK-4497 |
| Nominal voltage UN | 160 V                                                                               |                                                                       |         |
| Nominal current IN | 12 A                                                                                |                                                                       |         |
| mm²/AWG/kcmil      | 1.5                                                                                 |                                                                       |         |

|     |                                                                                     |         |  |
|-----|-------------------------------------------------------------------------------------|---------|--|
| EAC |  | B.01687 |  |
|-----|-------------------------------------------------------------------------------------|---------|--|

## PCB terminal block - MKDS 1/ 6-3,81 BK - 1800020

### Approvals

|                    |                                                                                   |                                                                                                                                                       |                 |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized   |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-19770427 |
|                    | B                                                                                 | D                                                                                                                                                     |                 |
| Nominal voltage UN | 300 V                                                                             | 300 V                                                                                                                                                 |                 |
| Nominal current IN | 10 A                                                                              | 10 A                                                                                                                                                  |                 |
| mm²/AWG/kcmil      | 30-16                                                                             | 30-16                                                                                                                                                 |                 |