

PCB terminal block - SMKDS 5/ 3-6,35 Z1L BD:17-19 - 1991927

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Number of positions per row: 3, product range: SMKDS 5, pitch: 6.35 mm, screw head form: Z1L Slotted Pozidriv, color: green, Pin layout: Linear pinning, Solder pin [P]: 5 mm, type of packaging: packed in cardboard



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 977078
GTIN	4017918977078
Weight per Piece (excluding packing)	8.440 g
Custom tariff number	85369010
Country of origin	Poland

Technical data

Item properties

Number of positions	3
Drive form screw head	Slotted Pozidriv (Z1L)
Screw thread	M3
Pin layout	Linear pinning

Material data - housing

Housing color	green (6021)
---------------	--------------

Dimensions for the product

Length [l]	18.5 mm
Width [w]	19.05 mm
Height [h]	26.5 mm
Pitch	6.35 mm
Height (without solder pin)	21.5 mm
Solder pin [P]	5 mm

PCB terminal block - SMKDS 5/ 3-6,35 Z1L BD:17-19 - 1991927

Technical data

Dimensions for PCB design

Hole diameter	1.3 mm
---------------	--------

Packaging information

Type of packaging	packed in cardboard
Pieces per package	50
Denomination packing units	Pcs.

Standards and Regulations

Connection in acc. with standard	EN-VDE
	CUL

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27440401
eCl@ss 11.0	27460101
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27261100
eCl@ss 6.0	27261100
eCl@ss 7.0	27440401
eCl@ss 9.0	27440401

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 6.0	EC002643
ETIM 7.0	EC002643

UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432

PCB terminal block - SMKDS 5/ 3-6,35 Z1L BD:17-19 - 1991927

Classifications

UNSPSC

UNSPSC 13.2	39121432
UNSPSC 18.0	39121432
UNSPSC 19.0	39121432
UNSPSC 20.0	39121432
UNSPSC 21.0	39121432

Approvals

Approvals

Approvals

SEV / EAC / cULus Recognized / IEC EE CB Scheme

Ex Approvals

Approval details

SEV		https://www.eurofins.ch/de/	IK-4497
Nominal voltage UN	450 V		
Nominal current IN	32 A		
mm²/AWG/kcmil	4		

EAC		B.01687
-----	---	---------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-19870331
	B	D	
Nominal voltage UN	250 V	300 V	
Nominal current IN	30 A	10 A	
mm²/AWG/kcmil	30-10	30-10	

PCB terminal block - SMKDS 5/ 3-6,35 Z1L BD:17-19 - 1991927

Approvals

IECEE CB Scheme			http://www.iecee.org/	CH-10787
Nominal voltage UN		450 V		
Nominal current IN		32 A		
mm ² /AWG/kcmil		4		