

Software - PC WORX UA SERVER-PLC 40 - 2402685

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



OPC UA server for communication with a maximum of 25 controllers

Product Description

The PC WORX UA SERVER provides the variables of controllers that have been programmed with PC Worx to all OPC UA clients. All variables are mapped in the server according to the PLCopen profile. The variable names are automatically synchronized from the current project. The server supports all security profiles via the binary profile, thereby enabling all access to be regulated. A user-friendly configurator guides you through the configuration of controllers and security settings. Diagnostic information regarding active communication can also be displayed from another computer using the configurator.

Your advantages

- Standardized access according to the PLCopen information model for IEC 61131-3
- Detailed diagnostic features
- Direct access to all data types, arrays, and complex structures supported by PC Worx.
- Transparent access to redundant controllers
- Safety configuration with support from tools



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 119441
GTIN	4055626119441
Weight per Piece (excluding packing)	60.000 g
Custom tariff number	49119900
Country of origin	Germany

Technical data

License information

Software - PC WORX UA SERVER-PLC 40 - 2402685

Technical data

License information

Intended use for the software	Runtime license
Type of license	Single-user license
Information regarding the type of license	License-free configurator. Server without license limited to one hour's runtime in demo mode
Information regarding the version	Valid for Version 1.1 (for features of older versions, please refer to the version information in the download area)
	The versions of devices, other software packages or the operating system must be kept up to date.

Functions

Basic functions	Data exchange according to DA profile spec 1.02 (2012)
	Security Policies: None, Basic128RSA15, Basic256
	Message Security: Mode none, sign, sign&encrypt
	Communication profile according to the PC-based server via binary protocol using TCP/IP
	Easy access to arrays and structures
	Variable mapping according to PLCopen profile spec 1.00
	Data exchange with up to 25 controllers
Supported controllers	ILC 1x1, AXC 1xxx, AXC 3xxx, PC WORX RT BASIC/SRT
Number of supported controllers	max. 25
Number of OPC items	max. 50000
Number of OPC items/controller	no limit, depends on the controller utilization
	typ. 500 (for AXC 1xxx and ILC 1x1)
	typ. 10000 (for AXC 3xxx, RFC 460R, and PC WORX BASIC/SRT)
Supported data types (standard)	BOOL, BYTE, INT, DINT, UINT, SINT, USINT, UDINT, WORD, DWORD, REAL, LREAL, STRING, TIME according to IEC 61709
Supported data types (user-defined)	ARRAY OF, STRUCTS, ARRAY OF STRUCT, STRUCT in STRUCT according to IEC 61131

Hardware requirements

RAM	min. 2 GByte
CPU	min. Intel® Core™ i3-2100 (2 GHz)
Interfaces	min. Gigabit Ethernet

Software requirements

Software	PC Worx Version 6 or later
Operating system	Windows® 7 (32-Bit/64-Bit)
	Windows® 8.1 (32-Bit/64-Bit)
	Windows® 10 (32-Bit/64-Bit)
	Windows® Server 2012

Software - PC WORX UA SERVER-PLC 40 - 2402685

Technical data

Software requirements

	Windows® Server 2016
Languages supported	English
Software platform	.NET Framework 4.5 (required for the configurator)
	.NET Framework 3.5 (required for server licensing)

General information

Information regarding the system requirements	Note the individual properties and requirements of the devices. Should you have any questions, please contact the Support team directly or the relevant contact person in Sales.
Information regarding the update rate	Guaranteed update rates greatly depend on the selected controller, the control capacity, and the selected PC.

Classifications

eCl@ss

eCl@ss 10.0.1	27242504
eCl@ss 11.0	27242504
eCl@ss 5.0	27242800
eCl@ss 5.1	27242800
eCl@ss 6.0	27242500
eCl@ss 7.0	27242504
eCl@ss 9.0	27242504

ETIM

ETIM 6.0	EC002537
ETIM 7.0	EC002537

UNSPSC

UNSPSC 13.2	43232403
UNSPSC 18.0	43232403
UNSPSC 19.0	43232403
UNSPSC 20.0	43232403
UNSPSC 21.0	43232403