

## I/O module - AXL F DO8/2 2A 1H - 2688381

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Axioline F, Digital output module, Digital outputs: 8, 24 V DC, 2 A, connection method: 2-conductor, transmission speed in the local bus: 100 Mbps, degree of protection: IP20, including bus base module and Axioline F connectors

### Product Description

The module is designed for use within an Axioline F station.  
It is used to output digital signals.  
The outputs are protected against short circuit and overload.

### Your advantages

- ✓ 8 digital outputs
- ✓ 24 V DC, 2 A
- ✓ Connection of actuators in 2-conductor technology
- ✓ Minimum update time of < 100 µs
- ✓ Device rating plate stored



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 046356 606479 |
| GTIN                                 | 4046356606479                                                                                           |
| Weight per Piece (excluding packing) | 180.000 g                                                                                               |
| Custom tariff number                 | 85389091                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|       |       |
|-------|-------|
| Width | 35 mm |
|-------|-------|

# I/O module - AXL F DO8/2 2A 1H - 2688381

## Technical data

### Dimensions

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Height             | 126.1 mm                                                                      |
| Depth              | 54 mm                                                                         |
| Note on dimensions | The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715). |

### Ambient conditions

|                                          |                                                   |
|------------------------------------------|---------------------------------------------------|
| Ambient temperature (operation)          | -25 °C ... 60 °C                                  |
| Ambient temperature (storage/transport)  | -40 °C ... 85 °C                                  |
| Permissible humidity (operation)         | 5 % ... 95 % (non-condensing)                     |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing)                     |
| Air pressure (operation)                 | 70 kPa ... 106 kPa (up to 3000 m above sea level) |
| Air pressure (storage/transport)         | 70 kPa ... 106 kPa (up to 3000 m above sea level) |
| Degree of protection                     | IP20                                              |

### Connection data

|                                       |                                                                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Designation                           | Axioline F connector                                                                                                          |
| Connection method                     | Push-in connection                                                                                                            |
| Note on the connection method         | Please observe the information provided on conductor cross sections in the "Axioline F: system and installation" user manual. |
| Conductor cross section solid min.    | 0.5 mm <sup>2</sup>                                                                                                           |
| Conductor cross section solid max.    | 1.5 mm <sup>2</sup>                                                                                                           |
| Conductor cross section flexible min. | 0.5 mm <sup>2</sup>                                                                                                           |
| Conductor cross section flexible max. | 1.5 mm <sup>2</sup>                                                                                                           |
| Conductor cross section AWG min.      | 20                                                                                                                            |
| Conductor cross section AWG max.      | 16                                                                                                                            |
| Stripping length                      | 8 mm                                                                                                                          |

### General

|                               |                                     |
|-------------------------------|-------------------------------------|
| Mounting type                 | DIN rail                            |
| Color                         | traffic grey A RAL 7042             |
| Net weight                    | 183.633 g                           |
| Note on weight specifications | with connectors and bus base module |
| Degree of pollution           | 2 (IEC 60664-1, EN 60664-1)         |
| Mounting position             | any (no temperature derating)       |

### Interfaces

|                      |                      |
|----------------------|----------------------|
| Designation          | Axioline F local bus |
| Number of interfaces | 2                    |
| Connection method    | Bus base module      |
| Transmission speed   | 100 Mbps             |

# I/O module - AXL F DO8/2 2A 1H - 2688381

## Technical data

### Axioline potentials

|                      |                                                                                                                                                                |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Designation          | Axioline F local bus supply ( $U_{Bus}$ )                                                                                                                      |
| Supply voltage       | 5 V DC (via bus base module)                                                                                                                                   |
| Current consumption  | max. 150 mA (up to HW 02)                                                                                                                                      |
|                      | max. 60 mA (as of HW 03)                                                                                                                                       |
| Power consumption    | max. 750 mW (up to HW 02)                                                                                                                                      |
|                      | max. 300 mW (as of HW 03)                                                                                                                                      |
| Designation          | Supply for digital output modules ( $U_O$ )                                                                                                                    |
| Supply voltage       | 24 V DC                                                                                                                                                        |
| Supply voltage range | 19.2 V DC ... 30 V DC (including all tolerances, including ripple)                                                                                             |
| Current consumption  | max. 16 A (Provide external protection; if the total current of 8 A is exceeded, connect the supply at the power connector parallel via both terminal points.) |
| Power consumption    | max. 480 W (of which 3.5 W are internal losses)                                                                                                                |
| Protective circuit   | Surge protection electronic (35 V, 0.5 s)                                                                                                                      |
|                      | Reverse polarity protection parallel diode; with external 5 A fuse (only for commissioning)                                                                    |
| Protection           | max. 16 A (polarity reversal protection up to 5 A)                                                                                                             |

### Digital outputs

|                                            |                                                                         |
|--------------------------------------------|-------------------------------------------------------------------------|
| Output name                                | Digital outputs                                                         |
| Connection method                          | Push-in connection                                                      |
| Connection technology                      | 2-conductor                                                             |
| Number of outputs                          | 8                                                                       |
| Protective circuit                         | Short-circuit protection, overload protection of the outputs electronic |
| Output voltage                             | 24 V                                                                    |
| Nominal output voltage                     | 24 V DC                                                                 |
| Nominal load, inductive                    | max. 48 VA (1.2 H, 12 $\Omega$ , at nominal load)                       |
| Nominal load, lamp                         | max. 48 W (at nominal voltage)                                          |
| Nominal load, ohmic                        | max. 48 W (12 $\Omega$ , at nominal load)                               |
| Switching frequency                        | max. 6000 per second (with nominal ohmic load, up to HW 02)             |
| Load min.                                  | 10 k $\Omega$                                                           |
| Output voltage when switched off           | max. 1 V                                                                |
| Output current when switched off           | max. 300 $\mu$ A                                                        |
| Behavior with overload                     | Shutdown with automatic restart                                         |
| Behavior with inductive overload           | Output can be destroyed                                                 |
| Reverse voltage resistance to short pulses | limited protection up to 0.5 A for 1 s                                  |

### Electrical isolation

# I/O module - AXL F DO8/2 2A 1H - 2688381

## Technical data

### Electrical isolation

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Test section | 5 V supply of the local bus ( $U_{BUS}$ ) / 24 V supply (I/Os) 500 V AC 50 Hz 1 min. |
|              | 5 V supply of the local bus ( $U_{BUS}$ ) / functional ground 500 V AC 50 Hz 1 min.  |
|              | 24 V supply (I/O) / functional ground 500 V AC 50 Hz 1 min.                          |

### Standards and Regulations

|                                    |                                                                                                                                                                                                  |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Immunity to ESD                    | Noise immunity test in accordance with EN 61000-6-2 Electrostatic discharge (ESD) EN 61000-4-2/IEC 61000-4-2 Criterion B, 6 kV contact discharge, 8 kV air discharge                             |
| Immunity to EF                     | Noise immunity test in accordance with EN 61000-6-2 Electromagnetic fields EN 61000-4-3/IEC 61000-4-3 Criterion A, Field intensity: 10 V/m                                                       |
| Immunity to burst                  | Noise immunity test in accordance with EN 61000-6-2 Fast transients (burst) EN 61000-4-4/IEC 61000-4-4 Criterion B, 2 kV                                                                         |
| Immunity to surge                  | Noise immunity test in accordance with EN 61000-6-2 Transient overvoltage (surge) EN 61000-4-5/IEC 61000-4-5 Criterion B, DC supply lines: $\pm 0.5$ kV/ $\pm 0.5$ kV (symmetrical/asymmetrical) |
| Immunity to conducted interference | Noise immunity test in accordance with EN 61000-6-2 Conducted interference EN 61000-4-6/IEC 61000-4-6 Criterion A, Test voltage 10 V                                                             |
| Interference emission              | Noise emission test according to EN 61000-6-3 Class B                                                                                                                                            |
| Mechanical tests                   | Vibration resistance in acc. with EN 60068-2-6/IEC 60068-2-6 5g                                                                                                                                  |
|                                    | Shock in acc. with EN 60068-2-27/IEC 60068-2-27 30g                                                                                                                                              |
|                                    | Continuous shock according to EN 60068-2-27/IEC 60068-2-27 10g                                                                                                                                   |
| Protection class                   | III (IEC 61140, EN 61140, VDE 0140-1)                                                                                                                                                            |
| Overvoltage category               | II (IEC 60664-1, EN 60664-1)                                                                                                                                                                     |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                      |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |


## Drawings

## I/O module - AXL F DO8/2 2A 1H - 2688381

Block diagram




Connection diagram




Internal wiring of the terminal points

Diagram




Maximum energy consumption of the outputs when switching off inductive loads with 100 % simultaneity

Diagram



Maximum energy consumption of the outputs when switching off inductive loads with 50 % simultaneity

Dimensional drawing



## I/O module - AXL F DO8/2 2A 1H - 2688381

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27242604 |
| eCl@ss 11.0   | 27242604 |
| eCl@ss 4.0    | 27240400 |
| eCl@ss 4.1    | 27240400 |
| eCl@ss 5.0    | 27242200 |
| eCl@ss 5.1    | 27242600 |
| eCl@ss 6.0    | 27242600 |
| eCl@ss 7.0    | 27242604 |
| eCl@ss 9.0    | 27242604 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001599 |
| ETIM 4.0 | EC001599 |
| ETIM 6.0 | EC001599 |
| ETIM 7.0 | EC001599 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 39121311 |
| UNSPSC 12.01  | 39121311 |
| UNSPSC 13.2   | 32151602 |
| UNSPSC 18.0   | 32151602 |
| UNSPSC 19.0   | 32151602 |
| UNSPSC 20.0   | 32151602 |
| UNSPSC 21.0   | 32151602 |

### Approvals

#### Approvals

---

##### Approvals

KR / NK / ABS / BSH / RINA / LR / PRS / BV / DNV GL / cULus Listed

---

##### Ex Approvals

---

## I/O module - AXL F DO8/2 2A 1H - 2688381

### Approvals

#### Approval details

|              |                                                                                     |                                                                                                                                                                                                                               |                   |
|--------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| KR           |    | <a href="http://www.krs.co.kr/eng/main/main.aspx">http://www.krs.co.kr/eng/main/main.aspx</a>                                                                                                                                 | HMB17372-AC002    |
| NK           | <b>ClassNK</b>                                                                      | <a href="http://www.classnk.or.jp/hp/en/">http://www.classnk.or.jp/hp/en/</a>                                                                                                                                                 | 14A006            |
| ABS          |                                                                                     | <a href="http://www.eagle.org/eagleExternalPortalWEB/">http://www.eagle.org/eagleExternalPortalWEB/</a>                                                                                                                       | 20-2059154-PDA    |
| BSH          |                                                                                     |                                                                                                                                                                                                                               | 840               |
| RINA         |    | <a href="http://www.rina.org/en">http://www.rina.org/en</a>                                                                                                                                                                   | ELE030120XG       |
| LR           |  | <a href="http://www.lr.org/en">http://www.lr.org/en</a>                                                                                                                                                                       | LR2001902TA       |
| PRS          |  | <a href="http://www.prs.pl/">http://www.prs.pl/</a>                                                                                                                                                                           | TE/1117/880590/20 |
| BV           |  | <a href="http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials">http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials</a> | 36433/B2 BV       |
| DNV GL       |  | <a href="https://approvalfinder.dnvgl.com/">https://approvalfinder.dnvgl.com/</a>                                                                                                                                             | TAA00000DF        |
| cULus Listed |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>                                                                         | FILE E 238705     |

## I/O module - AXL F DO8/2 2A 1H - 2688381

### Accessories

#### Accessories

#### Device marking

Insert label - EMT (35X28)R - 0801602



Insert label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: snapped into marker carrier, lettering field size: 35 x 28 mm, Number of individual labels: 500

---

#### DIN rail connector

Bus connector - AXL F BS H - 2700992



Axioline F bus base module for housing type H

---

#### Terminal marking

Zack marker strip - ZB 20,3 AXL UNPRINTED - 0829579



Zack marker strip for Axioline F (device labeling), in 2 x 20.3 mm pitch, unprinted, 25-section, for individual labeling with B-STIFT 0.8, X-PEN, or CMS-P1-PLOTTER

---

Zack Marker strip, flat - ZBF 10/5,8 AXL UNPRINTED - 0829580



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into flat marker groove, for terminal block width: 10.15 mm, lettering field size: 4 of 10.15 x 5 mm and 1 of 5.8 x 5 mm, Number of individual labels: 50