

## Power cable - PLD E 608-CA-3,0/FS/UL - 2702306

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Power cable, 3-position, PVC, gray RAL 7001, free cable end, on Socket straight, coding: black, cable length: 3 m, with UL approval

### Product Description

The cable serves to connect 600 class PLD enclosure lights to the supply voltage.

### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 113319
GTIN	4055626113319
Weight per Piece (excluding packing)	320.000 g
Custom tariff number	85444290
Country of origin	Germany

### Technical data

#### Dimensions

Length of cable	3 m
Stripping length of the free conductor end	32 mm (Protective conductor (PE) 39 mm)

#### Ambient conditions

Ambient temperature (operation)	-5 °C ... 40 °C
Degree of protection	IP20
	IP40 (plugged in)

#### General

Rated current at 40°C	16 A
-----------------------	------

# Power cable - PLD E 608-CA-3,0/FS/UL - 2702306

## Technical data

### General

Rated voltage	250 V AC
Number of positions	3
Coding	black
Insertion/withdrawal cycles	100

### Material

Material, knurls	not available
------------------	---------------

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 10.0.1	27060311
eCl@ss 11.0	27060311
eCl@ss 4.0	27378000
eCl@ss 4.1	27378000
eCl@ss 5.0	27379100
eCl@ss 5.1	27379100
eCl@ss 6.0	27279200
eCl@ss 7.0	27279218
eCl@ss 9.0	27060311

### ETIM

ETIM 6.0	EC001855
ETIM 7.0	EC001855

### UNSPSC

UNSPSC 13.2	39131505
UNSPSC 19.0	31251501
UNSPSC 20.0	31251501
UNSPSC 21.0	31251501

## Approvals

### Approvals

# Power cable - PLD E 608-CA-3,0/FS/UL - 2702306

## Approvals

### Approvals

UL Recognized / cUL Recognized / cULus Recognized

---

### Ex Approvals

---

### Approval details

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 118976
cUL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 118976
cULus Recognized			

## Accessories

### Accessories

#### Installation connector

Connector - PLD E 608-CO-MS - 2702308



Connector for series connection, black, 3-pos.

---

#### Power distributor

T distributor - PLD E 608-CO-MS/FS/FR - 2702310



T-distributor with 2 sockets and one connector for series connection, black, 3-pos.

## Power cable - PLD E 608-CA-3,0/FS/UL - 2702306

### Accessories

---

---

Phoenix Contact 2021 © - all rights reserved  
<http://www.phoenixcontact.com>