

## Inline function terminal - IB IL 24 FLM-PAC - 2736903

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Inline, Branch terminal, for extending the Inline local bus to Inline or Fieldline Modular, transmission speed in the local bus: 500 kbps / 2 Mbps, degree of protection: IP20, including Inline connector and labeling field

### Your advantages

- ✓ Connection of Fieldline Modular M8 to Fieldline Modular M12
- ✓ Connection of Fieldline Modular M8 or M12 to Inline Modular

### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 079204
GTIN	4046356079204
Weight per Piece (excluding packing)	88.400 g
Custom tariff number	85389091
Country of origin	Germany

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

Width	12.2 mm
Height	136.8 mm
Depth	71.5 mm

#### Ambient conditions

## Inline function terminal - IB IL 24 FLM-PAC - 2736903

### Technical data

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	75 % (On average, 85 % occasionally)
Permissible humidity (storage/transport)	75 % (On average, 85 % occasionally)
Air pressure (operation)	80 kPa ... 106 kPa (up to 2000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection	IP20

#### Interfaces

Designation	Inline local bus
No. of channels	1 (incoming local bus)
Connection method	Inline data jumper
Transmission speed	500 kbps / 2 Mbps (Can be used in Inline stations with these transmission speeds)
Designation	Inline local bus
Connection method	Inline shield connector
Transmission speed	500 kbps / 2 Mbps

#### General

Mounting type	DIN rail
Color	green
Net weight	43 g

#### Standards and Regulations

Connection in acc. with standard	CUL
Protection class	III (IEC 61140, EN 61140, VDE 0140-1)


#### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

### Drawings


# Inline function terminal - IB IL 24 FLM-PAC - 2736903

Connection diagram



## Inline function terminal - IB IL 24 FLM-PAC - 2736903

Dimensional drawing



### Classifications

#### eCl@ss

eCl@ss 4.0	27250200
eCl@ss 4.1	27250200
eCl@ss 5.0	27250200
eCl@ss 5.1	27242600
eCl@ss 6.0	27242600
eCl@ss 7.0	27242608
eCl@ss 8.0	27242608
eCl@ss 9.0	27242608

#### ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC001604
ETIM 6.0	EC001604
ETIM 7.0	EC001604

# Inline function terminal - IB IL 24 FLM-PAC - 2736903

## Classifications

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	32151602

## Approvals

### Approvals

#### Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

#### Ex Approvals

UL Listed / cUL Listed / cULus Listed

### Approval details

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 140324
---------------	--	---	---------------

cUL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 140324
----------------	--	---	---------------

EAC		EAC-Zulassung
-----	--	---------------

cULus Recognized	
------------------	--

## Accessories

### Accessories

## Inline function terminal - IB IL 24 FLM-PAC - 2736903

### Accessories

#### I/O component

Inline terminal - IB IL 24 SEG/F-D-PAC - 2861904



Inline segment terminal block, complete with accessories (connector and labeling field), 24 V DC, with fuse and diagnostics

---

### Plug

Inline shield connector - IB IL SCN-6 SHIELD - 2726353



Inline shield connector

---

### Remote bus cable

Remote bus cable - IBS RBC METER/F-T - 2723123



By the meter, Remote bus cable, INTERBUS, shielded, PUR halogen-free, may green RAL 6017, 6-wire (3 x 2 x 0.22 mm<sup>2</sup>), color single wire: Green-yellow, white-brown, gray-pink, flexible installation

Remote bus cable - IBS RBC METER-T - 2806286



By the meter, Remote bus cable, INTERBUS, shielded, PVC, may green RAL 6017, 6-wire (3 x 2 x 0.22 mm<sup>2</sup>), color single wire: Green-yellow, white-brown, gray-pink, fixed installation