

Patch cable - FL CAT5 PATCH 2,0 - 2832289

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Patch cable, CAT5, assembled, 2 m



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 044011 |
| GTIN | 4046356044011 |
| Weight per Piece (excluding packing) | 87.840 g |
| Custom tariff number | 85444210 |
| Country of origin | Poland |

Technical data

Cable type

| | |
|--------------------|--------|
| Fixed cable length | 2.00 m |
| Shielding | SF/UTP |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -10 °C ... 60 °C |
|---------------------------------|------------------|

External sheath

| | |
|------------------------|---------|
| Outer sheath, material | LSFROH |
| External diameter | 5.50 mm |
| External diameter max. | 6.2 mm |

Single wire

Patch cable - FL CAT5 PATCH 2,0 - 2832289

Technical data

Single wire

| | |
|----------------------------|----------------------|
| Single wires, quantity | 8 |
| Single wire, material | Cu litz wire |
| Single wire, cross section | 0.14 mm ² |

Plug

| | |
|--------------------|------|
| Connection profile | RJ45 |
|--------------------|------|

Mechanical properties

| | |
|---|-------|
| Smallest bending radius, fixed installation | 30 mm |
|---|-------|

General

| | |
|---|-------------------------|
| Conductor length | 2.00 m |
| Nominal voltage U _N | 150 V _{rms} |
| Transmission characteristics (category) | CAT5 |
| Transmission speed | 1 Gbps |
| Degree of protection | IP20 |
| Contact resistance | ≤ 0.003 Ω (IEC 60603-7) |

Behavior in fire

| | |
|------------------------|------------------------------|
| Flame resistance | according to IEC 60332-3C |
| Concentration of fumes | in accordance with IEC 61034 |
| Halogen-free | according to IEC 60754-1 |

Standards and Regulations

| | |
|--|------------------------------|
| Concentration of fumes | in accordance with IEC 61034 |
| Flame resistance | according to IEC 60332-3C |
| Halogen-free | according to IEC 60754-1 |
| Flammability rating according to UL 94 | V0 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27060308 |
| eCl@ss 11.0 | 27060308 |
| eCl@ss 4.0 | 27250500 |
| eCl@ss 4.1 | 27250500 |
| eCl@ss 5.0 | 27259200 |

Patch cable - FL CAT5 PATCH 2,0 - 2832289

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27259200 |
| eCl@ss 6.0 | 27259200 |
| eCl@ss 7.0 | 27060308 |
| eCl@ss 9.0 | 27060308 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001262 |
| ETIM 3.0 | EC001262 |
| ETIM 4.0 | EC001262 |
| ETIM 6.0 | EC001262 |
| ETIM 7.0 | EC001262 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 26121609 |
| UNSPSC 7.0901 | 26121609 |
| UNSPSC 11 | 26121609 |
| UNSPSC 12.01 | 26121609 |
| UNSPSC 13.2 | 26121604 |
| UNSPSC 18.0 | 26121604 |
| UNSPSC 19.0 | 26121604 |
| UNSPSC 20.0 | 26121604 |
| UNSPSC 21.0 | 26121604 |

Approvals

Approvals

Approvals

DNV GL / EAC / EAC-RoHS

Ex Approvals

Approval details

| | | | |
|--------|--|---|------------|
| DNV GL | | https://approvalfinder.dnvgl.com/ | TAE000020G |
|--------|--|---|------------|

Patch cable - FL CAT5 PATCH 2,0 - 2832289

Approvals

| | | |
|-----|---|----------|
| EAC |  | 19060508 |
|-----|---|----------|

| | | |
|----------|---|------------|
| EAC-RoHS |  | B.00385/20 |
|----------|---|------------|

Accessories

Accessories

Color-coding

Color-coding - FL PATCH CCODE BK - 2891194



Color marking for patch cable, black

Color-coding - FL PATCH CCODE BN - 2891495



Color marking for patch cable, brown

Color-coding - FL PATCH CCODE BU - 2891291



Color marking for patch cable, blue

Patch cable - FL CAT5 PATCH 2,0 - 2832289

Accessories

Color-coding - FL PATCH CCODE GN - 2891796



Color marking for patch cable, green

Color-coding - FL PATCH CCODE GY - 2891699



Color marking for patch cable, gray

Color-coding - FL PATCH CCODE RD - 2891893



Color marking for patch cable, red

Color-coding - FL PATCH CCODE VT - 2891990



Color marking for patch cable, purple

Color-coding - FL PATCH CCODE YE - 2891592



Color marking for patch cable, yellow

Safety locking

Patch cable - FL CAT5 PATCH 2,0 - 2832289

Accessories

Port Guard Security Element - FL PATCH GUARD - 2891424



Lockable security element

Port Guard Security Element - FL PATCH SAFE CLIP - 2891246



Security element for FL patch cable
