

Relay base - PR3-BSC1/2X21 - 2833602

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Relay base PR3..., for REL-OR octal relays with 2 changeover contacts, screw connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5




Your advantages

- Relay base family for assembly with a 2- or 3-changeover contact relay



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| GTIN |  4 017918 933821 |
| GTIN | 4017918933821 |
| Weight per Piece (excluding packing) | 60.540 g |
| Custom tariff number | 85366990 |
| Country of origin | China |

Technical data

Dimensions

| | |
|------------------------------|-----------------|
| Width | 38 mm |
| Height | 75 mm |
| Depth with retaining bracket | 84 mm (EL3-M52) |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

Connection data, input side

Relay base - PR3-BSC1/2X21 - 2833602

Technical data

Connection data, input side

| | |
|----------------------------------|--|
| Connection name | Input side |
| Connection method | Screw connection |
| Stripping length | 10 mm |
| Screw thread | M3 |
| Conductor cross section solid | 0.2 mm ² ... 2.5 mm ² |
| | 0.2 mm ² ... 2.5 mm ² (2 conductors with the same cross-section) |
| Conductor cross section flexible | 0.2 mm ² ... 2.5 mm ² |
| | 0.2 mm ² ... 2.5 mm ² (2 conductors with the same cross-section) |
| Conductor cross section AWG | 26 ... 14 |
| | 26 ... 14 (2 conductors with the same cross-section) |

Connection data, output side

| | |
|----------------------------------|--|
| Connection name | Output side |
| Connection method | Screw connection |
| Stripping length | 10 mm |
| Screw thread | M3 |
| Conductor cross section solid | 0.2 mm ² ... 2.5 mm ² |
| | 0.2 mm ² ... 2.5 mm ² (2 conductors with the same cross-section) |
| Conductor cross section flexible | 0.2 mm ² ... 2.5 mm ² |
| | 0.2 mm ² ... 2.5 mm ² (2 conductors with the same cross-section) |
| Conductor cross section AWG | 26 ... 14 |
| | 26 ... 14 (2 conductors with the same cross-section) |

General

| | |
|--------------------------------|-------------|
| Nominal voltage U _N | 400 V AC/DC |
| Nominal current I _N | 10 A |
| Color | green |
| Mounting position | any |

Standards and Regulations

| | |
|----------------------------------|-----|
| Connection in acc. with standard | CSA |
|----------------------------------|-----|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Relay base - PR3-BSC1/2X21 - 2833602

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371100 |
| eCl@ss 4.1 | 27371100 |
| eCl@ss 5.0 | 27371600 |
| eCl@ss 5.1 | 27371600 |
| eCl@ss 6.0 | 27371600 |
| eCl@ss 7.0 | 27371603 |
| eCl@ss 9.0 | 27371603 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001456 |
| ETIM 3.0 | EC001456 |
| ETIM 4.0 | EC001456 |
| ETIM 6.0 | EC001456 |
| ETIM 7.0 | EC001456 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211917 |
| UNSPSC 7.0901 | 39121516 |
| UNSPSC 11 | 39121516 |
| UNSPSC 12.01 | 39121516 |
| UNSPSC 13.2 | 39122326 |
| UNSPSC 18.0 | 39122335 |
| UNSPSC 19.0 | 39122335 |
| UNSPSC 20.0 | 39122335 |
| UNSPSC 21.0 | 39122335 |

Accessories

Necessary add-on products

Single relay - REL-OR- 24DC/2X21 - 2834232



Plug-in octal relays with power contacts, 2 changeover contacts, test button, mechanical switching position indicator, coil voltage: 24 V DC

Relay base - PR3-BSC1/2X21 - 2833602

Accessories

Single relay - REL-OR- 24AC/2X21 - 2834245



Plug-in octal relays with power contacts, 2 changeover contacts, test button, mechanical switching position indicator, coil voltage: 24 V AC

Single relay - REL-OR-120AC/2X21 - 2834258



Plug-in octal relays with power contacts, 2 changeover contacts, test button, mechanical switching position indicator, coil voltage: 120 V AC

Single relay - REL-OR-230AC/2X21 - 2834261



Plug-in octal relays with power contacts, 2 changeover contacts, test button, mechanical switching position indicator, coil voltage: 230 V AC
