

Slave protocol chip - IBS SUPI 4 TQFP - 2988117

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Slave protocol chip, for INTERBUS



RoHS

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	160 pc
GTIN	 4 046356 341752
GTIN	4046356341752
Weight per Piece (excluding packing)	3.880 g
Custom tariff number	85423290
Country of origin	Japan

Technical data

Dimensions

Width	10 mm
Height	1 mm
Depth	10 mm
Length	10 mm

Ambient conditions

Ambient temperature (storage/transport)	-65 °C ... 150 °C (at max. 60 %)
Ambient temperature (operation)	-40 °C ... 85 °C (at max. 75% humidity during operation)

Module

IC power supply voltage	3.3 V DC $\pm$ 10 % (DC)
-------------------------	--------------------------

Slave protocol chip - IBS SUPI 4 TQFP - 2988117

Technical data

Module

Typical current consumption	20 mA
Connection method	Remote bus, local bus or installation remote bus
Interface	INTERBUS
Internal data length	64 bytes IN/64 bytes OUT
User interface	MFP interface, digital I/O (16 IN/16 OUT, 32 IN, 32 OUT), parallel and serial port for microprocessors

General

Type	TQFP 64
------	---------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27242605
eCl@ss 11.0	27242605
eCl@ss 4.0	27250200
eCl@ss 4.1	27250200
eCl@ss 5.0	27249200
eCl@ss 5.1	27249200
eCl@ss 6.0	27242600
eCl@ss 7.0	27242608
eCl@ss 9.0	27242605

ETIM

ETIM 2.0	EC001433
ETIM 3.0	EC001601
ETIM 4.0	EC001601
ETIM 6.0	EC001601
ETIM 7.0	EC001601

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404

Slave protocol chip - IBS SUPI 4 TQFP - 2988117

Classifications

UNSPSC

UNSPSC 13.2	32151602
UNSPSC 18.0	32151602
UNSPSC 19.0	32151602
UNSPSC 20.0	32151602
UNSPSC 21.0	32151602