

## Connecting bridge - C-ME 4/2 - 3035759

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Connection bridge, for connecting 2 test disconnect terminal blocks



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 046356 521857
GTIN	4046356521857
Weight per Piece (excluding packing)	1.050 g
Custom tariff number	85389099
Country of origin	Poland

### Technical data

#### General

Number of positions	2
Color	orange
Material	PA
Flammability rating according to UL 94	V0

#### Dimensions

Width	12.2 mm
Length	5.2 mm
Height	23.8 mm

#### Ambient conditions

# Connecting bridge - C-ME 4/2 - 3035759

## Technical data

### Ambient conditions

Operating temperature	-60 °C ... 85 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 10.0.1	27141190
eCl@ss 11.0	27141190
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141190
eCl@ss 9.0	27141192

### ETIM

ETIM 3.0	EC000313
ETIM 4.0	EC002498
ETIM 6.0	EC002848
ETIM 7.0	EC002848

### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410
UNSPSC 18.0	31162903

## Connecting bridge - C-ME 4/2 - 3035759

### Classifications

#### UNSPSC

UNSPSC 19.0	31162903
UNSPSC 20.0	31162903
UNSPSC 21.0	31162903