

Latching - UPR/ 2 - 3045567

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Latching, length: 39.8 mm, width: 10 mm, number of positions: 2, color: orange

Your advantages

- ✔ Can be used in all plug versions
- ✔ Snapped into the outside of the plug housing and hooks onto the terminal block housing when the plug is snapped on



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 046356 055765
GTIN	4046356055765
Weight per Piece (excluding packing)	1.240 g
Custom tariff number	85369010
Country of origin	Poland

Technical data

General

Number of positions	2
Color	orange
Material	PA-GF
Flammability rating according to UL 94	V2

Dimensions

Width	10 mm
-------	-------

Latching - UPR/ 2 - 3045567

Technical data

Dimensions

Length	39.8 mm
--------	---------

General

Relative insulation material temperature index (Elec., UL 746 B)	65 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	115 °C

Standards and Regulations

Flammability rating according to UL 94	V2
----------------------------------------	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27141190
eCl@ss 11.0	27141190
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141190
eCl@ss 9.0	27141190

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002498
ETIM 6.0	EC002848
ETIM 7.0	EC002848

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121410

Latching - UPR/ 2 - 3045567

Classifications

UNSPSC

UNSPSC 18.0	39121410
UNSPSC 19.0	39121410
UNSPSC 20.0	39121410
UNSPSC 21.0	39121410