

Ring cable lug - C-RCI 6/M4 - 3240027

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Ring cable lug, yellow, 4 ... 6 mm², M4

Your advantages

- ✓ The sleeves are conically tapered to facilitate easy and correct insertion of the conductor
- ✓ The insulated ring cable lugs with plastic sleeve are hard-soldered and feature the 'EASY ENTRY' system



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| GTIN |  4 046356 452045 |
| GTIN | 4046356452045 |
| Weight per Piece (excluding packing) | 2.000 g |
| Custom tariff number | 85369010 |
| Country of origin | China |

Technical data

Dimensions

| | |
|---|---------|
| Length (b) | 26.7 mm |
| Width (a) | 9.5 mm |
| Maximum stripping length | 9 mm |
| Length of insulation sleeve (c) | 14 mm |
| Inner dimension of the insulating collar (d) | 6.6 mm |
| Distance between the center and the insulation sleeve (e) | 8 mm |

Ring cable lug - C-RCI 6/M4 - 3240027

Technical data

Dimensions

| | |
|------------------------|--------|
| Inner diameter (f) | 4.3 mm |
| Material thickness (g) | 1 mm |

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 105 °C |
| Ambient temperature (assembly) | -20 °C ... 100 °C |
| Optimum ambient temperature (storage/transport) | 20 °C 50 % Humidity (RH), store inside sealed original packaging. Avoid direct sunlight and heat. |
| Short-term temperature | 100 °C |

General

| | |
|---------------------|--------------|
| Color | yellow |
| Stripping length | 9 mm |
| Components | halogen-free |
| Material | Copper |
| Insulating material | PA |
| Coating | tin-plated |

Standards and Regulations


| | |
|--|--------------|
| Flammability rating according to UL 94 | V2 |
| Design according to standard | JIS, UL, CSA |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Drawings

Dimensional drawing



Ring cable lug - C-RCI 6/M4 - 3240027

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27400204 |
| eCl@ss 11.0 | 27400204 |
| eCl@ss 4.0 | 27060700 |
| eCl@ss 4.1 | 27060700 |
| eCl@ss 5.0 | 27400200 |
| eCl@ss 5.1 | 27400200 |
| eCl@ss 6.0 | 27400200 |
| eCl@ss 7.0 | 27400204 |
| eCl@ss 9.0 | 27400204 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC001052 |
| ETIM 6.0 | EC001052 |
| ETIM 7.0 | EC001052 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 27113201 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11 | 27121703 |
| UNSPSC 12.01 | 27121703 |
| UNSPSC 13.2 | 27121707 |
| UNSPSC 18.0 | 27121707 |
| UNSPSC 19.0 | 27121707 |
| UNSPSC 20.0 | 27121707 |
| UNSPSC 21.0 | 27121707 |