

## Connector - C-SCF 1,5/4,8X0,8 - 3240155

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Slip-on sleeve, non-insulated, 0.75 ... 1.5 mm<sup>2</sup>, 4.8 x 0.8


The figure shows a version of the article

### Your advantages

- ✓ They round out the product range in terms of connectors
- ✓ The uninsulated slip-on sleeves and flat plugs are made from electrolytically tin-plated brass



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	100 pc
GTIN	 4 046356 453721
GTIN	4046356453721
Weight per Piece (excluding packing)	0.400 g
Custom tariff number	85369010
Country of origin	Germany

### Technical data

#### Dimensions

Length (b)	15.6 mm
Width (a)	4.8 mm
Maximum stripping length	7 mm
Material thickness (g)	0.4 mm

#### Ambient conditions

# Connector - C-SCF 1,5/4,8X0,8 - 3240155

## Technical data

### Ambient conditions

Ambient temperature (operation)	110 °C
---------------------------------	--------

### General


Color	silver
Stripping length	7 mm
Components	halogen-free
Material	Brass
Insulating material	nicht zutreffend
Coating	tin-plated

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Drawings

Dimensional drawing



## Classifications

### eCl@ss

eCl@ss 10.0.1	27400212
eCl@ss 11.0	27400212
eCl@ss 4.0	27060700
eCl@ss 4.1	27060700
eCl@ss 5.0	27400200
eCl@ss 5.1	27400200
eCl@ss 6.0	27400200
eCl@ss 7.0	27400204
eCl@ss 9.0	27400212

## Connector - C-SCF 1,5/4,8X0,8 - 3240155

### Classifications

#### ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC001052
ETIM 6.0	EC001059
ETIM 7.0	EC001059

#### UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121707
UNSPSC 19.0	27121707

### Accessories

#### Accessories

##### Crimping tool

Crimping pliers - CRIMPFOX-SC 1,5 - 1212048



Crimping pliers, for non-insulated slip-on sleeves 2.8 and 4.8 mm, 0.1 - 1.5 mm<sup>2</sup>, B crimp

Crimping pliers - CRIMPFOX-SC 1,5-M - 1212725



Crimping pliers, for non-insulated slip-on sleeves 2.8 and 4.8 mm, 0.1 - 1.5 mm<sup>2</sup>, B crimp

## Connector - C-SCF 1,5/4,8X0,8 - 3240155

### Accessories

Crimping pliers - CRIMPFOX-SC 6 - 1212050



Crimping pliers, for uninsulated slip-on sleeves 2.8, 4.8, and 6.3 mm, 0.5 - 6 mm<sup>2</sup>, B crimp

---

### Die

Replacement die - CF 500/DIE SC 1,5 - 1212241



Die for crimping machine CF 500, for slip-on sleeves and flat connectors (C-SCF... and C-SCM...) 0.1 ... 1.5 mm<sup>2</sup>

Replacement die - CF 500/DIE SC 6 - 1212242



Die for crimping machine CF 500, for slip-on sleeves and flat connectors (C-SCF... and C-SCM...) 0.5 ... 6 mm<sup>2</sup>

---

### Insulating sleeve

Insulating sleeve - PT/FS 4,8 - 1670497



Insulating sleeve, as touch protection, for 4.8 mm slip-on sleeves, slide onto the conductor before