

Toolbox - CRIMPFOX 4 IN 1 SET

1200102

<https://www.phoenixcontact.com/us/products/1200102>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Tool for processing ferrules according to DIN 46228-4, 0.5 mm² to 2.5 mm², equipped with pressure lock, cutting, stripping, twisting, and crimping unit, with three magazines including a strip each of ferrules from 0.5 mm² ... 2.5 mm², packaged in a robust plastic case

Your advantages

- Robust and durable due to use of resistant plastics and annealed metals
- Multifunctional crimping pliers for the processing of Taped ferrules according to DIN 46228-4
- Integrated pressure lock ensures consistently high-quality crimping
- Up to 30% time savings since the process steps required for assembling conductors can be carried out using only one tool
- Visualized process flows directly on the pliers simplify operation

Commercial Data

| | |
|--------------------------------------|---------------------|
| Item number | 1200102 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales Key | B14 |
| Product Key | BH3511 |
| Catalog Page | Page 415 (C-3-2019) |
| GTIN | 4055626042398 |
| Weight per Piece (including packing) | 735.2 g |
| Weight per Piece (excluding packing) | 727.7 g |
| Customs tariff number | 82032000 |
| Country of origin | DE |

Toolbox - CRIMPFOX 4 IN 1 SET

1200102

<https://www.phoenixcontact.com/us/products/1200102>



Technical Data

Notes

Environmental Product Compliance

California Proposition 65

Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration

Product properties

| | |
|--------------------|---------------------|
| Product type | Crimping tool |
| Compression | Indent crimp |
| Min. cross section | 0.5 mm ² |
| Max. cross section | 2.5 mm ² |
| AWG min | 20 |
| AWG max | 14 |

Connection data

Conductor connection

| | |
|-----------------------------|---|
| Cross section range, metric | 0.5 mm ² ... 2.5 mm ² |
| Cross section range AWG | 20 ... 14 |
| Stripping length | 11 mm |

Dimensions

| | |
|--------|---------|
| Width | 31.5 mm |
| Height | 100 mm |
| Length | 180 mm |

Material specifications

| | |
|-------|-------|
| Color | black |
|-------|-------|

Toolbox - CRIMPFOX 4 IN 1 SET

1200102

<https://www.phoenixcontact.com/us/products/1200102>



Approvals



EAC

Approval ID: RU x-DE.xx08.B.02974

Toolbox - CRIMPFOX 4 IN 1 SET

1200102

<https://www.phoenixcontact.com/us/products/1200102>



Classifications

ECLASS

| | |
|---------------|----------|
| ECLASS-9.0 | 21043811 |
| ECLASS-10.0.1 | 21043811 |
| ECLASS-11.0 | 21043811 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000168 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 27111500 |
|-------------|----------|

Toolbox - CRIMPFOX 4 IN 1 SET

1200102

<https://www.phoenixcontact.com/us/products/1200102>



Accessories

Magazine

Magazine - CRIMPFOX 4 IN 1/MAG - 1200103

<https://www.phoenixcontact.com/us/products/1200103>




Ferrule magazine for CRIMPFOX 4 IN 1, for ferrules with insulating collars from 0.5 mm² ... 2.5 mm², with a length of 8 mm

Ferrule

Ferrule - AI 0,5-8 WH S1 - 1200104

<https://www.phoenixcontact.com/us/products/1200104>



Taped ferrules, 0.5 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, white, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Toolbox - CRIMPFOX 4 IN 1 SET

1200102


<https://www.phoenixcontact.com/us/products/1200102>



Ferrule

Ferrule - AI 0,75- 8 GY S1 - 1200105

<https://www.phoenixcontact.com/us/products/1200105>




Taped ferrules, 0.75 mm^2 , sleeve length 8 mm, with plastic collar, according to DIN 46228-4, gray, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule

Ferrule - AI 1,0-8 RD S1 - 1200106

<https://www.phoenixcontact.com/us/products/1200106>



Taped ferrules, 1.0 mm^2 , sleeve length 8 mm, with plastic collar, according to DIN 46228-4, red, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Toolbox - CRIMPFOX 4 IN 1 SET

1200102

<https://www.phoenixcontact.com/us/products/1200102>



Ferrule

Ferrule - AI 1,5-8 BK S1 - 1200107

<https://www.phoenixcontact.com/us/products/1200107>




Taped ferrules, 1.5 mm^2 , sleeve length 8 mm, with plastic collar, according to DIN 46228-4, black, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule

Ferrule - AI 2,5-8 BU S1 - 1200108

<https://www.phoenixcontact.com/us/products/1200108>



Taped ferrules, 2.5 mm^2 , sleeve length 8 mm, with plastic collar, according to DIN 46228-4, blue, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 40 sleeves per strip.

Toolbox - CRIMPFOX 4 IN 1 SET




1200102

<https://www.phoenixcontact.com/us/products/1200102>

Ferrule

Ferrule - AI 0,75- 8 BU S1 - 1200163

<https://www.phoenixcontact.com/us/products/1200163>




Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, sleeve length: 8 mm, length: 14 mm, color: blue, number of strips: 10, number of sleeves per strip: 50

Ferrule

Ferrule - AI 2,5-8 GY S1 - 1200164

<https://www.phoenixcontact.com/us/products/1200164>



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, sleeve length: 8 mm, length: 14 mm, color: gray, number of strips: 10, number of sleeves per strip: 40

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com