


# Ferrule - AI 0,75- 8 BU S1

1200163

<https://www.phoenixcontact.com/us/products/1200163>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, sleeve length: 8 mm, length: 14 mm, color: blue, number of strips: 10, number of sleeves per strip: 50

## Commercial Data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1200163             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 500 pc              |
| Sales Key                            | B16                 |
| Product Key                          | BH3415              |
| Catalog Page                         | Page 415 (C-3-2019) |
| GTIN                                 | 4055626166551       |
| Weight per Piece (including packing) | 0.091 g             |
| Weight per Piece (excluding packing) | 0.091 g             |
| Customs tariff number                | 85369010            |
| Country of origin                    | DE                  |

# Ferrule - Al 0,75- 8 BU S1

1200163

<https://www.phoenixcontact.com/us/products/1200163>



## Technical Data

### Product properties


|                    |                                                 |
|--------------------|-------------------------------------------------|
| Product type       | Ferrule                                         |
| Conductor category | stranded conductors, class 2, 5, 6 / B, C, K, M |

### Connection data

#### Conductor connection

|                                       |                      |
|---------------------------------------|----------------------|
| Conductor cross section flexible max. | 0.75 mm <sup>2</sup> |
| Conductor cross section AWG max.      | 18                   |
| Stripping length                      | 11 mm                |

### Dimensions

|                                           |                                                                                     |
|-------------------------------------------|-------------------------------------------------------------------------------------|
| Dimensional drawing                       |  |
| Length                                    | 14 mm                                                                               |
| Sleeve length                             | 8 mm                                                                                |
| Maximum stripping length                  | 11 mm                                                                               |
| Ferrule diameter                          | 1.3 mm                                                                              |
| Sleeve wall thickness                     | 0.15 mm                                                                             |
| Insulating collar thickness               | 0.25 mm                                                                             |
| Inner dimensions of the insulating collar | 2.8 mm                                                                              |

### Material specifications

|                                        |                                |
|----------------------------------------|--------------------------------|
| Color                                  | blue                           |
| Material                               | CU-DHP                         |
| Flammability rating according to UL 94 | HB                             |
| Coating                                | tin-plated (galvanic)          |
| Components                             | free from silicone and halogen |

### Mechanical properties

#### Technical data

|               |      |
|---------------|------|
| Sleeve length | 8 mm |
|---------------|------|

### Environmental and real-life conditions

#### Ambient conditions

|                        |                                             |
|------------------------|---------------------------------------------|
| Permanent temperature  | 105 °C (-40 °C no load / 0 °C dynamic load) |
| Short-term temperature | 120 °C                                      |

# Ferrule - Al 0,75- 8 BU S1

1200163

<https://www.phoenixcontact.com/us/products/1200163>



## Standards and regulations

|                              |             |
|------------------------------|-------------|
| Design according to standard | DIN 46228-4 |
|------------------------------|-------------|

# Ferrule - Al 0,75- 8 BU S1


1200163

<https://www.phoenixcontact.com/us/products/1200163>



## Drawings

Dimensional drawing



# Ferrule - Al 0,75- 8 BU S1

1200163

<https://www.phoenixcontact.com/us/products/1200163>



## Approvals



**CSA**

Approval ID: 247397

# Ferrule - Al 0,75- 8 BU S1

1200163

<https://www.phoenixcontact.com/us/products/1200163>



## Classifications

### ECLASS

|               |          |
|---------------|----------|
| ECLASS-9.0    | 27400201 |
| ECLASS-10.0.1 | 27400201 |
| ECLASS-11.0   | 27400201 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC000005 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 27121700 |
|-------------|----------|

# Ferrule - Al 0,75- 8 BU S1

1200163

<https://www.phoenixcontact.com/us/products/1200163>



## Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

# Ferrule - Al 0,75- 8 BU S1

1200163

<https://www.phoenixcontact.com/us/products/1200163>



## Accessories

### Multi-function tool

Multi-function tool - CRIMPFOX 4 IN 1 - 1200101

<https://www.phoenixcontact.com/us/products/1200101>



Tool for processing ferrules according to DIN 46228-4, 0.5 mm<sup>2</sup> to 2.5 mm<sup>2</sup>, equipped with pressure lock, magazine, cutting, stripping, twisting, and crimping unit.

---

Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)