

# Crimp insert - CF 500/DIE RCI 6

1212240

<https://www.phoenixcontact.com/us/products/1212240>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Die for crimping machine CF 500, for insulated cable lugs (C ... RCI... and C ... FCI...) 0.5 ... 6 mm<sup>2</sup>

## Commercial Data

Item number	1212240
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	B15
Product Key	BH323Z
Catalog Page	Page 511 (C-3-2019)
GTIN	4046356449977
Weight per Piece (including packing)	76.1 g
Weight per Piece (excluding packing)	76 g
Customs tariff number	84799070
Country of origin	DE

# Crimp insert - CF 500/DIE RCI 6



1212240

<https://www.phoenixcontact.com/us/products/1212240>

## Technical Data

### Product properties

Product type	Die
Compression	Oval crimp
Min. cross section	0.5 mm <sup>2</sup>
Max. cross section	6 mm <sup>2</sup>

### Connection data

#### Conductor connection

Cross section range, metric	0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>
-----------------------------	---

### Material specifications

Color	silver
-------	--------

### Cable / line

External cable diameter	0.9 mm ... 2.9 mm
-------------------------	-------------------

# Crimp insert - CF 500/DIE RCI 6



1212240

<https://www.phoenixcontact.com/us/products/1212240>

## Approvals



**EAC**

Approval ID: RU C-DE.AI30.B.01549

# Crimp insert - CF 500/DIE RCI 6



1212240

<https://www.phoenixcontact.com/us/products/1212240>

## Classifications

### ECLASS

ECLASS-9.0	17139201
ECLASS-11.0	17130192
ECLASS-10.0.1	17139201

### ETIM

ETIM 8.0	EC002778
----------	----------

### UNSPSC

UNSPSC 21.0	27111500
-------------	----------

# Crimp insert - CF 500/DIE RCI 6

1212240

<https://www.phoenixcontact.com/us/products/1212240>




## Accessories

### Covering hood

Covering hood - CF 500/COV RCI - 1212255

<https://www.phoenixcontact.com/us/products/1212255>



Protective cover for crimping machine CF 500, for insulated cable lugs 0.14 - 6 mm<sup>2</sup> (RCI 1.5/6) and turned contacts 0.14 - 4 mm<sup>2</sup> (TC 4)

---

Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)