

Stripping machine - WF 1000 120V



1212258

<https://www.phoenixcontact.com/us/products/1212258>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Stripping machine with integrated graphic display, for conductors and cables up to 6 mm in diameter, 120 V version

Your advantages

- Multi-strand cables with a diameter of up to 6 mm can also be stripped
- The stripping dimensions are set individually via knobs and are shown on the large display
- Partial stripping is supported
- The clamping force automatically adjusts itself to the required extraction force
- Compact stripping machine for automatically stripping conductors with a cross section of 0.08 to 6 mm²
- Pressure points on sensitive insulation are avoided
- Even special types of insulation, such as PTFE and silicone, can be stripped in addition to standard types

Commercial Data

Item number	1212258
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	B15
Product Key	BH3221
Catalog Page	Page 407 (C-3-2019)
GTIN	4046356457019
Weight per Piece (including packing)	99.99 g
Weight per Piece (excluding packing)	11,092 g
Customs tariff number	84798100
Country of origin	DE

Stripping machine - WF 1000 120V



1212258

<https://www.phoenixcontact.com/us/products/1212258>

Technical Data

Product properties

Product type	Stripping machine
Compression	trapezoidal
Partial stripping length	2 mm ... 20 mm
Insertion length minimum	15 mm
Maximum throughput	6
Min. cross section	0.08 mm ²
Max. cross section	6 mm ²

Electrical properties

Frequency range	60 Hz
Power consumption	160 VA
Nominal voltage U _N	120 V

Supply

Supply voltage range	120 V
----------------------	-------

Connection data

Conductor connection

Cross section range, metric	0.08 mm ² ... 6 mm ²
Cross section range AWG	28 ... 10
Stripping length	2 mm ... 20 mm

Dimensions

Width	141 mm
Height	221 mm
Length	363 mm
Diameter	6 mm
Diameter, conductor entry opening	6 mm

External dimensions

Outside diameter	6 mm
------------------	------

Cable / line

External cable diameter	≤ 6 mm
-------------------------	--------

Stripping machine - WF 1000 120V

1212258

<https://www.phoenixcontact.com/us/products/1212258>



Approvals



EAC

Approval ID: RU C-DE.AI30.B.01549

Stripping machine - WF 1000 120V



1212258

<https://www.phoenixcontact.com/us/products/1212258>

Classifications

ECLASS

ECLASS-10.0.1	17130102
ECLASS-9.0	17130102
ECLASS-11.0	17130102

ETIM

ETIM 8.0	EC002778
----------	----------

UNSPSC

UNSPSC 21.0	27111500
-------------	----------

Stripping machine - WF 1000 120V



1212258

<https://www.phoenixcontact.com/us/products/1212258>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Stripping machine - WF 1000 120V

1212258

<https://www.phoenixcontact.com/us/products/1212258>



Accessories

Spare knife

Spare knife - WF 1000/SB - 1212279

<https://www.phoenixcontact.com/us/products/1212279>

Spare knife for stripping machine



Replacement retaining jaw

Replacement retaining jaw - WF 1000/CJ - 1212415

<https://www.phoenixcontact.com/us/products/1212415>

Replacement jaws for stripping machine



Stripping machine - WF 1000 120V

1212258

<https://www.phoenixcontact.com/us/products/1212258>



Accessories for tools/automatic devices

Accessories for tools/automatic devices - WF 1000/COV - 1212417

<https://www.phoenixcontact.com/us/products/1212417>

Waste holder for stripping machine



Accessories for tools/automatic devices

Accessories for tools/automatic devices - WF 1000/TR - 1212416

<https://www.phoenixcontact.com/us/products/1212416>

Start key trigger for stripping machine



Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com