


1019532  
<https://www.phoenixcontact.com/us/products/1019532>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Distribution block, nom. voltage: 690 V, nominal current: 24 A, number of connections: 12, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: gray

Your advantages

- Space savings of up to 50 % on the DIN rail, thanks to transverse mounting
- Flexible use, thanks to DIN rail mounting, direct mounting or adhesive mounting
- Time-saving conductor connection, thanks to tool-free Push-in direct connection technology
- Time savings of up to 80 %, thanks to ready-to-mount blocks without manual bridging
- Clear wiring, thanks to eleven different color variants

Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1019532       |
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 10 pc         |
| Sales key                            | BE09          |
| Product key                          | BEA214        |
| GTIN                                 | 4055626506432 |
| Weight per piece (including packing) | 22.43 g       |
| Weight per piece (excluding packing) | 19.539 g      |
| Customs tariff number                | 85369010      |
| Country of origin                    | PL            |

# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## Technical data

### Product properties

|                       |                            |
|-----------------------|----------------------------|
| Product type          | Distributor terminal block |
| Number of positions   | 1                          |
| Number of connections | 12                         |
| Number of rows        | 1                          |
| Potentials            | 1                          |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 0.77 W |

### Connection data

|                                                                                                                   |                                                                                 |
|-------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| Number of connections per level                                                                                   | 12                                                                              |
| Nominal cross section                                                                                             | 2.5 mm <sup>2</sup>                                                             |
| Stripping length                                                                                                  | 8 mm ... 10 mm                                                                  |
| Internal cylindrical gage                                                                                         | A3                                                                              |
|                                                                                                                   | B3                                                                              |
| Connection in acc. with standard                                                                                  | IEC 60947-7-1                                                                   |
| Conductor cross section rigid                                                                                     | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup>                                      |
| Cross section AWG                                                                                                 | 26 ... 12 (converted acc. to IEC)                                               |
| Conductor cross section flexible                                                                                  | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                    |
| Conductor cross section, flexible [AWG]                                                                           | 26 ... 14 (converted acc. to IEC)                                               |
| Conductor cross-section flexible (ferrule without plastic sleeve)                                                 | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                    |
| Flexible conductor cross section (ferrule with plastic sleeve)                                                    | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                    |
| Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve) | 1.5 mm <sup>2</sup>                                                             |
| Nominal current                                                                                                   | 24 A                                                                            |
| Maximum load current                                                                                              | 32 A (with 4 mm <sup>2</sup> conductor cross-section)                           |
| Maximum total current                                                                                             | The maximum load current of the individual terminal point must not be exceeded. |
| Nominal voltage                                                                                                   | 690 V                                                                           |
| Note                                                                                                              | The IEC 60947-7-1 standard applies for the use of mounting accessories.         |
| Nominal cross section                                                                                             | 2.5 mm <sup>2</sup>                                                             |
| Connection in acc. with standard                                                                                  | IEC 60998-2-2                                                                   |
| Nominal voltage                                                                                                   | 450 V (in accordance with IEC 60998-2-2)                                        |

### Connection cross sections directly pluggable

|                               |                                           |
|-------------------------------|-------------------------------------------|
| Conductor cross section rigid | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup> |
|-------------------------------|-------------------------------------------|

# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

|                                                                   |                                   |
|-------------------------------------------------------------------|-----------------------------------|
| Conductor cross section, rigid [AWG]                              | 20 ... 12 (converted acc. to IEC) |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.75 mm² ... 2.5 mm²              |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 0.5 mm² ... 2.5 mm²               |

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 31.1 mm |
| Height             | 45.7 mm |
| Depth              | 29.2 mm |
| Depth on NS 35/7,5 | 30.9 mm |

## Material specifications

|                                                                         |        |
|-------------------------------------------------------------------------|--------|
| Color                                                                   | gray   |
| Flammability rating according to UL 94                                  | V0     |
| Insulating material group                                               | I      |
| Insulating material                                                     | PA     |
| Static insulating material application in cold                          | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C |

## Mechanical properties

### Mechanical data

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

## Environmental and real-life conditions

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)                                                     |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|                                  | IEC 60998-2-2 |

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# PTVFIX 12X2,5-NS35A GY - Distribution block

1019532

<https://www.phoenixcontact.com/us/products/1019532>



## Drawings

Circuit diagram



# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1019532>

|  <b>CSA</b><br>Approval ID: 158887 |                       |                       |                   |                             |
|---------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                     | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                         | 300 V                 | 20 A                  | 26 - 12           | -                           |
| Use group C                                                                                                         | 300 V                 | 20 A                  | 26 - 12           | -                           |
| Use group D                                                                                                         | 600 V                 | 5 A                   | 26 - 12           | -                           |

|  <b>cULus Recognized</b><br>Approval ID: E60425 |                       |                       |                   |                             |
|----------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                                      | 300 V                 | 20 A                  | 26 - 12           | -                           |
| Use group C                                                                                                                      | 300 V                 | 20 A                  | 26 - 12           | -                           |
| Use group F                                                                                                                      | 500 V                 | 20 A                  | 26 - 12           | -                           |
| Use group D                                                                                                                      | 600 V                 | 5 A                   | 26 - 12           | -                           |

| <b>DNV</b><br>Approval ID: TAE00004R4 |  |  |  |  |
|---------------------------------------|--|--|--|--|
|---------------------------------------|--|--|--|--|

# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250118 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## Accessories



Note: Applying some accessories below might limit this product.

### FBS 2-5 - Plug-in bridge

3030161

<https://www.phoenixcontact.com/us/products/3030161>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, length: 23 mm, color: red



Max. current carrying capacity: 24 A

### FBS 2-5 BU - Plug-in bridge

3036877

<https://www.phoenixcontact.com/us/products/3036877>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: blue



Max. current carrying capacity: 24 A

## PTVFIX 12X2,5-NS35A GY - Distribution block

1019532

<https://www.phoenixcontact.com/us/products/1019532>



### FBS 2-5 GY - Plug-in bridge

3038969

<https://www.phoenixcontact.com/us/products/3038969>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: gray

 Max. current carrying capacity: 24 A

---

### NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/us/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/us/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/us/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/us/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/us/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/us/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/us/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## PTVFIX 12X2,5-NS35A GY - Distribution block

1019532

<https://www.phoenixcontact.com/us/products/1019532>



### NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/us/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

### NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/us/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/us/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/us/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

## PTVFIX 12X2,5-NS35A GY - Distribution block

1019532

<https://www.phoenixcontact.com/us/products/1019532>



### NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/us/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

---

### NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/us/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# PTVFIX 12X2,5-NS35A GY - Distribution block



1019532

<https://www.phoenixcontact.com/us/products/1019532>

## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/us/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/us/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## PTVFIX 12X2,5-NS35A GY - Distribution block

1019532

<https://www.phoenixcontact.com/us/products/1019532>



### NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/us/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

### NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/us/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# PTVFIX 12X2,5-NS35A GY - Distribution block

1019532

<https://www.phoenixcontact.com/us/products/1019532>



## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/us/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)