

NT24k®-16TX-POE Industrial PoE+ Switch

N-Tron® Networking Series



▶▶▶ Industrial Managed Gigabit PoE+ Switch

Red Lion's N-Tron® series NT24k®-16TX-POE industrial managed Gigabit Ethernet switch features 16 10/100/1000Base-T(X) ports and IEEE802.3af/at (PoE+), providing a robust solution for transmitting power and data to equipment in harsh environments.

Housed in a compact, hardened DIN-rail enclosure, the NT24k-16TX-POE managed switch features 16 Gigabit ports, redundant 22-49 VDC power inputs, high shock and vibration tolerance and a wide -40° to 80°C operating temperature range. Rugged, reliable and easy to use, the NT24k-16TX-POE switch offers a 240 Watt PoE budget that can be allocated to any of its 16 ports, up to 30 Watts per port.



APPLICATIONS

- > Alternative Energy
- > Manufacturing
- > Oil & Gas
- > Transportation
- > Water/Wastewater

PRODUCT HIGHLIGHTS

- > IEEE 802.3af/at output up to 30 Watts per port/ 240 Watts per switch
- > Smart Plug-and-Play Operation
- > 22 to 49 VDC Redundant Power Inputs
- > Wide -40° to 80°C Operating Temperature
- > Robust Remote Monitoring
- > N-Ring™ and N-Link™ Network Ring Technology

IEEE 1588v2 PTP OPTIONS

- Boundary Clock
- Transparent Clock

IEEE 1588v2 applications include

- Coordinated motion control
- Time-stamped data logging
- Time-stamped fault detection

PTP Models & Upgrade Kit Available

FEATURES & BENEFITS

- > 16 Copper Ports
 - 10/100/1000Base-T(X) copper ports
- > Redundant 22 to 49 VDC Power Inputs
 - Boosts power to meet PoE+ output requirements
- > IEEE 802.3af/at PoE Output
 - 240 Watt PoE budget configurable across all 16 ports, up to 30 Watts per port
- > Extended Environmental Specifications
 - Wide -40° to 80°C operating temperature range
 - Ultra-reliable > 2 million hours MTBF
 - UL/cUL: Class I, Div. 2 Groups A, B, C and D
- > Plug-and-Play Operation
 - IGMP auto-configuration
 - MDIX auto-sensing cable
 - Simple network ring configuration
 - Backup and restore via recovery card or XML
- > Fully Managed Networking Functionality
 - SSH/SSL/HTTPS
 - SNMP v1, v2, v3
 - Web browser management
 - Detailed ring map and fault location charting
 - RSTP - 802.1d, 802.1w, 802.1D
 - Trunking and port mirroring
 - 802.1Q tag VLAN and port VLAN
 - IEEE 802.1x with RADIUS remote server authentication
 - DHCP Server, Option 82 relay, Option 61, IP fallback
 - Port Security – MAC address based
 - 802.1p QoS, port QoS and DSCP
 - Event log/Syslog
 - SNTP (Simple Network Time Protocol)
 - IEEE 1588v2 (PTP) models available
 - Multi-Member N-Ring technology with ~30ms healing
 - N-Link redundant ring technology
 - N-View™ monitoring technology
 - EtherNet/IP™ CIP™ messaging
 - 802.1AB-2005 LLDP (Link Layer Discovery Protocol)

industrial
networking



EtherNet/IP®

▶▶▶ NT24k-16TX-POE Specifications

SWITCH PROPERTIES

Operation: Managed
Number of MAC Addresses: 16,000
IEEE Compliant: 802.3, 802.3u, 802.3ab, 802.3x, 802.3af/at,
802.1d/D/w, 802.1p, 802.1Q, 802.1x
IEEE 1588v2 Software-Based Option
Latency (Typical): 1.6 μ s
Switching Method: Store-and-Forward
PoE Budget: Configurable up to 240 Watts
Up to 30 Watts per port (25.5 at the PD)
LED Status Indicators
Configurable Alarm Contact
Onboard Temperature Sensor
Supports Full/Half Duplex Operation
Maximum Throughput: Up to 32 Gb/s
MDIX Auto Sensing Cable
Auto Sensing Speed and Flow Control
Communications: Full Wire Speed
MTBF: >2 million hours
Jumbo Frame Support

POWER INPUT

Input Voltage: 22-49 VDC
Steady Input Current: 11.24 A @ 24 VDC
Inrush: 67 A / .096 ms @ 24 VDC
BTU/HR: 122

POWER OVER ETHERNET

PoE Standard: IEEE 802.3af/at Gigabit PSE
PoE Budget: Configurable up to 240 Watts
Up to 30 Watts per port (25.5 at the PD)
PoE Output Power: 57 VDC
Power Pin Assignment: Pins 1/2 (-), Pins 3/6 (+)
PSE Type: Type 2

CONNECTORS

10/100/1000BaseT: Sixteen (16) RJ-45 ports
ESD and surge protection diodes on all copper ports
Configuration Port: One (1) USB Type B

NETWORK MEDIA

10BaseT: $\geq$ Cat3 cable
100BaseTX: $\geq$ Cat5 cable
1000BaseT: $\geq$ Cat5e cable

RECOMMENDED WIRING CLEARANCE

Front: 2" (5.08 cm)
Top: 4" (10.16 cm)

ENVIRONMENTAL

Operating Temperature: -40°C to 80°C
Storage Temperature: -40°C to 85°C
Operating Humidity: 10% to 95% (non condensing)
Operating Altitude: 0 to 10,000 ft.
Shock: 200 g @ 10 ms (bulkhead mounted)
Vibration: 50 g @ 5-200 Hz, Triaxial (bulkhead mounted)

CERTIFICATION & COMPLIANCE

Product Safety:
ANSI/ISA 12.12.01-2013 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations
UL508 Industrial Control Equipment
CAN/CSA-C22.2 No. 213-M1987 Class I Div. 2 Hazardous Locations
CAN/CSA-C22.2 No. 14-M1987 Industrial Control Equipment
Emissions:
FCC Title 47, Part 15, Radio Frequency Devices, Subpart B ANSI C63.4-2009; Industry Canada ICES-003, EN 55011; EN 61000-6-4, EN 61000-3-2, EN61000-3-3, EN 55032
Immunity:
EN 55024, EN 61000-6-2; IEC 61000-4-2 (ESD); IEC 61000-4-3 (RFAM); IEC 61000-4-4 (EFT); IEC 61000-4-5 (SURGE); IEC 61000-4-6 (RFCEM); IEC 61000-4-8 (PFMF); IEC 61000-4-11 (VDI)
Rail:
EN 50155, EN 50121 and EN 61373
Designed to Comply with:
IEEE 1613 (Electric Utility Substations), NEMA TS1/TS2 (Traffic Control)
Other:
ABS Type Approval for Shipboard Applications; EMC Directive 2014/30/EU; LV Directive 2014/35/EU GOST-R, RoHS Compliant

MECHANICAL

Case Dimensions:
Height: 5.88" (14.92 cm)
Width: 4.28" (10.88 cm)
Depth: 5.54" (14.07 cm)
Weight: 3.25 lbs (1.48 kg)
Mount: DIN Rail 35 mm

WARRANTY


3 Years on Design and Manufacturing Defects

ORDERING GUIDE

MODEL NUMBER	DESCRIPTION
NT24K-16TX-POE	16 Port 10/100/1000BaseT Managed PoE+ Industrial Ethernet Switch
NT24K-16TX-POE-PT	16 Port 10/100/1000BaseT Managed PoE+ Industrial Ethernet Switch, PTP Enabled
NTCD-CFG	NT24k Configuration Recovery Device
NTPS-24-20	DIN-Rail Power Supply 20 Amp @ 24 VDC
NTPS-48-10	DIN-Rail Power Supply 10 Amp @ 48 VDC
NT24K-NM-PMK	NT24k Non-Modular Panel Mount Kit
NT24K-KIT-PTP	NT24k Upgrade License to Enable IEEE 1588/PTP on Non-PT NT24k Switches

▶▶▶ NT24k-16TX-POE Specifications

DIMENSIONS



All specifications are subject to change. Consult the company website for more information.