

**Rittal – The System.**

Faster – better – everywhere.



# SV 3451.505

## Conductor terminal

State: 3/14/2022 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 3451.505 - Conductor terminal Push-in

For connecting round conductors.

## Features

Benefits	Maintenance-free Time-saving plug-on mounting Terminal housing with integrated labeling fields Universal conductor terminals
Applications	For use as a busbar pick-off terminals for L, N, or PE conductors in switchgear or control systems as well as conductor connection terminal in meter enclosures. For mounting on E-Cu or CUPONAL busbars
Function principle	Fully insulated terminal for tool-free connection of conductors Conductor is released by the integral release pin
Material	Polyamide Fire protection corresponding to UL 94-V0
Color	RAL 7042
Test specification	IEC 60 999-1 IEC 60 947-7-1/-2
Connection of round conductors, fine wire with wire end ferrule	1.5 - 16 mm <sup>2</sup>
Connection of round conductors, fine wire without wire end ferrule	1.5 - 16 mm <sup>2</sup>
Connection of round conductors, multi-wire	1.5 - 16 mm <sup>2</sup>
Connection of round conductors, single-wire	1.5 - 16 mm <sup>2</sup>
For busbar thickness	5 mm 0.2 "
Weight/packaging unit	0.23 kg 0.5 lb.
Packaging unit	10 Stück

# Features

---

ETIM 7.0	EC000001
----------	----------

---

ECLASS 8.0	27141146
------------	----------

# Approvals

---

Approvals	DNV-GL UR + C-UR
-----------	---------------------

---

Explanations	Declaration of conformity
--------------	---------------------------