

**Rittal – The System.**



Faster – better – everywhere.



**SV 3568.005**

**Laminated Copper Bar**

State: 3/14/2022 (Source: [ittal.com/us-en](http://ittal.com/us-en))



ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# SV 3568.005 - Laminated Copper Bar

Cu lamina made of high-purity electrolyte copper, length: 2000 mm/bar.

## Features

Material	Cu lamina: High-purity electrolyte copper Insulation: Highly resistant vinyl blend, expansion 370%, temperature: -30°C ... +105°C, fire protection according to UL-94 V0, dielectric strength: 20 kV/mm
Length	2,000 mm 78.7 "
Rated current for temperature increase 50 K	350 A
Rated current for temperature increase 30 K	265 A
Rated current for temperature increase 70 K	415 A
Note	Assembly = number of layers x layer width x layer thickness May be cut to length as required The conductor temperature of the laminated copper bar is derived by adding the ambient temperature and the temperature increase together. Example: 3565.005 carrying 180 A, i.e. the temperature increases by 30 K. At an ambient temperature of 35 °C, this produces a resultant conductor temperature of 35 °C + 30 K = 65 °C.
Laminated flat copper version	Number of lamina: 6 Lamina width: 15.5 mm Lamina thickness: 0.8 mm Lamina width: 0.61 " Lamina thickness: 0.03 "
Weight/packaging unit	1.83 kg 4 lb.
Packaging unit	1 Stück
ETIM 7.0	EC001522
ECLASS 8.0	27370303

# Approvals

---

Approvals	C-UR UR UR + C-UR
-----------	-------------------------

---

Certificates	EAC
--------------	-----

---

Explanations	Declaration of conformity
--------------	---------------------------