

Rittal – The System.

Faster – better – everywhere.



SV 3585.020

Busbars CUPONAL

Stand: 3/14/2022 (Quelle: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 3585.020 - Busbars CUPONAL

Copper-coated aluminum busbars.

Eigenschaften

Product description	Copper-coated aluminum busbars, suitable for configuring busbar systems with busbar supports SV 9340.000/SV 9340.050.
Material	Aluminum Copper
Length	2,400 mm 94.5 "
Rated current max.	363 A
Note	The rated current is generated at 65°C rail temperature and 35°C ambient temperature Correction factor diagram according to DIN EN 43 671 May be cut to length as required
Standards	DIN EN 13 601
Cross-section	Flat copper bar width: 20 mm Flat copper bar thickness: 10 mm Flat copper bar width: 0.79 " Flat copper bar thickness: 0.39 "
Weight/packaging unit	19.5 kg 43 lb.
Packaging unit	3 Stück
ETIM 7.0	EC001522
ECLASS 8.0	27370303

Approbationen

Erklärungen

Declaration of conformity