

Universal light with integral motion detector

Benefits:

- Insulated plastic housing
- Efficient compact fluorescent tube
- Simple attachment of the light to the enclosure

Material:

- Plastic

Supply includes:

- Mounting clips



Also required:

- Connection accessories, see page 755



Technical specifications	Socket	Width mm	Height mm	Depth mm	Model No.	Approvals
18 W, 110 – 240 V, 50 – 60 Hz	Earthing-pin	343	95	55	4155.110	VDE
	-	343	95	55	4155.010	VDE
	-	343	95	55	4155.510	UL

Courtesy light

without door-operated switch

Technical specifications	Socket	Width mm	Height mm	Depth mm	Model No.	Approvals
14 W, 100 – 240 V, 50/60 Hz	Earthing-pin	452	117	50	4139.140	ENEC
18 W, 100 – 240 V, 50/60 Hz	Earthing-pin	682	117	50	4139.180	ENEC
30 W, 100 – 240 V, 50/60 Hz	Earthing-pin	987	117	50	4139.300	ENEC

with door-operated switch

Technical specifications	Socket	Width mm	Height mm	Depth mm	Model No.	Approvals
14 W, 100 – 240 V, 50/60 Hz	Earthing-pin	452	117	50	4139.150	ENEC
18 W, 100 – 240 V, 50/60 Hz	Earthing-pin	682	117	50	4139.190	ENEC
30 W, 100 – 240 V, 50/60 Hz	Earthing-pin	987	117	50	4139.350	ENEC



Also required:

- Connection accessories, see page 755

