

Door/locks

Hinges



Hinges 180°

for TS bayed enclosure suites with comfort handle

In TS bayed enclosure suites with comfort handle for semi-cylinder, the following door opening angles may be achieved:
Sheet steel door: max. 180°
Glazed door: max. 140°

Material:
Die-cast zinc

Colour:
RAL 7035/RAL 9005

Supply includes:
Assembly screws.

Version for	Packs of	Model No. TS	
		RAL 7035	RAL 9005
Sheet steel door	4	7824.520	7824.522
Glazed door	4	7824.525	–

Note:

- The protection category of the enclosure may be reduced.
- Not for divided doors.
- Door hinge remains the same within a bayed enclosure suite.
- Not suitable for use with TS designer glazed doors.



Rear panel bracket

For:

- Premium Panel
- Premium Line KL, from height 200 mm

For fitting on the inside, so that there are no exterior surfaces where substances could accumulate and pose a potential threat to hygiene. Holds the rear panel against the enclosure when it is flipped down; easily removed if required.

Packs of	Model No. CP
1 set	6682.000

Material:

Stainless steel 1.4301 (AISI 304)

Supply includes:

Assembly parts.



Cover hinge

for KL

The cover hinge is simply screwed to the enclosure protection channel and to the edge fold.

Supply includes:

Assembly parts.

Material	Packs of	Model No. KL
Die-cast zinc	6	1592.000
Stainless steel 1.4404 (AISI 316L)	2	1592.010



Cover retainer

for KL

The cover retainer is easily fitted without drilling, and allows the covers to be opened upwards, even when the terminal box below is bayed.

Packs of	Model No. KL
3 pairs	1591.000

Hinges

B

7.4