

Door/locks

Door, internal

Support strips


For attachment of

- Cable trunking
- Cable conduit holders
- Contact hazard protection covers
- Equipment installed on the door
- Cable clamping and attachment

4.5 mm diameter hole on a 25 mm DIN pitch pattern.



For TS, CM, ES, TP



For AE

Material:

Sheet steel, zinc-plated, passivated

Supply includes:

Packs of 20, including screws.



Accessories:

Screws and self-tapping screws M5, see page 1011.

For door width mm	Length mm	Model No. SZ
400	290	4594.000
500	390	4309.000
600	490	4596.000
800	690	4598.000
900	790	4579.000
1000	890	4599.000

For enclosures AE	Model No. SZ
1007.500 ²⁾ , 1013.500 ²⁾ 1018.500 ²⁾ , 1019.500 ²⁾ 1050.500 ¹⁾ , 1057.500 1100.500, 1110.500 1114.500 ¹⁾ , 1130.500 1213.500 ¹⁾ , 1350.500 ¹⁾	2325.000
1009.500 ²⁾ , 1010.500 ²⁾ 1012.500 ²⁾ , 1039.500 1054.500, 1058.500 1060.500, 1076.500 1090.500, 1260.500 ¹⁾ 1339.500, 1360.500 1376.500	2326.000
1014.500 ²⁾ , 1073.500 1077.500	2327.000
1016.500 ²⁾ , 1017.500 ²⁾ 1055.500, 1180.500 1280.500 ¹⁾	2328.000

¹⁾ For these AE models, the door rails should be cut to length.

²⁾ Only in conjunction with perforated mounting strips (see page 965).

Spacers

The universal assembly component for all cases where a distance from the mounting level is required. With self-tapping thread for diameter 4.5 mm. The following components may be attached to the rear using 5.5 x 13 mm screws:

- Top-hat/cross rails
- Contact hazard protection covers
- Master switch trim panels
- Cable clamp rails, etc.

Material:

Hexagonal steel (SW8)

Surface finish:

Zinc-plated, passivated



Accessories:

Screws 5.5 x 13 mm, see page 1011.



Length mm	Packs of	Model No. TS
25	12	2311.225
50	12	2311.250

