

Rittal – The System.

Faster – better – everywhere.



AX 6315.150

AX compact control cabinet

State: 9/16/2022 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AX 6315.150 - AX compact control cabinet Operating housing AX with handle strips

The command panel with handle strips based on AX, carbon steel, with support arm cut-out Ø 130 mm to match the support arm system CP 60/120/180, service access optionally from front or rear, aluminum front panel can be easily removed for machining, protection category IP 55.

Features

Model No.	AX 6315.150
Product description	The command panel with handle strips based on AX, carbon steel, with support arm cut-out Ø 130 mm to match the support arm system CP 60/120/180, service access optionally from front or rear, aluminum front panel can be easily removed for machining, protection category IP 55.
Material	Housing: Carbon steel Door: Carbon steel, all-round foamed-in PU seal Front panel: Aluminum Cover caps: Plastic
Surface finish	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Handle strip: Natural anodized Front panel: Natural anodized.
Color	Housing and door: RAL 7035 Handle strip: Natural anodized Front panel: Natural anodized. Cover caps: Similar to RAL 7024
Supply includes	Housing with cut-out and reinforcement for support arm connection Ø 130 mm Front with maximum cut-out, covered with easily machinable 3 mm aluminum front panel Side handle strips with cover caps Integral interior mounting bracket with system punchings Cam lock with 3 mm double-bit insert

Features

Dimensions	Width: 300 mm Height: 300 mm Depth: 210 mm Width: 11.8 " Height: 11.8 " Depth: 8.27 "
Protection category NEMA	NEMA 1, 12
Type rating according to UL 50E	Type 1, 12
Servicing access version	From the front
IK code	IK08
Note	<p>The support arm connection and door catch may be swapped over by rotating the enclosure</p> <p>Optional: Support arm connection Ø 130 mm, preformed off-center in the reinforcement plate, easily drilled out</p> <p>Lock systems for servicing access from the rear: The lock insert may be exchanged for AX Mini Comfort Handle Type A 27 mm lock inserts</p> <p>Lock systems for servicing access from the front: Lock insert may be exchanged for 27 mm lock inserts, type A</p>
Base material	Carbon steel
Note on Model No.:	Compatible mounting plate 5051.368 with shipping bag 5051.300
Packaging unit	1 pc(s).
Weight/packaging unit	7 kg 15.4 lb.
Copper weight (kg per piece)	0
Customs tariff number	94032080
EAN	4028177923232
ETIM 7.0	EC002504
ECLASS 8.0	27180505

Approvals

Approvals

GOST
UL + C-UL (listed)

Explanations

Declaration of conformity
Declaration of conformity UK