

# Rittal – The System.

Faster – better – everywhere.



## AX 6320.650

## AX compact control cabinet

State: 9/16/2022 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AX 6320.650 - AX compact control cabinet Operating housing AX with handle strips

The command panel with handle strips based on AX, carbon steel, with support arm cut-out Ø 130 mm to match the support arm system CP 60/120/180, service access optionally from front or rear, aluminum front panel can be easily removed for machining, protection category IP 55.

## Features

Model No.	AX 6320.650
Product description	The command panel with handle strips based on AX, carbon steel, with support arm cut-out Ø 130 mm to match the support arm system CP 60/120/180, service access optionally from front or rear, aluminum front panel can be easily removed for machining, protection category IP 55.
Material	Housing: Carbon steel Door: Carbon steel, all-round foamed-in PU seal Front panel: Aluminum Cover caps: Plastic
Surface finish	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Handle strip: Natural anodized Front panel: Natural anodized.
Color	Housing and door: RAL 7035 Handle strip: Natural anodized Front panel: Natural anodized. Cover caps: Similar to RAL 7024
Supply includes	Housing with cut-out and reinforcement for support arm connection Ø 130 mm Front with maximum cut-out, covered with easily machinable 3 mm aluminum front panel Side handle strips with cover caps Integral interior mounting bracket with system punchings Cam lock with 3 mm double-bit insert

# Features

---

Dimensions	Width: 600 mm Height: 600 mm Depth: 210 mm Width: 23.6 " Height: 23.6 " Depth: 8.27 "
Protection category NEMA	NEMA 1, 12
Type rating according to UL 50E	Type 1, 12
Servicing access version	From the rear
IK code	IK08
Note	The support arm connection and door catch may be swapped over by rotating the enclosure Optional: Support arm connection Ø 130 mm, preformed off-center in the reinforcement plate, easily drilled out Lock systems for servicing access from the rear: The lock insert may be exchanged for AX Mini Comfort Handle Type A 27 mm lock inserts Lock systems for servicing access from the front: Lock insert may be exchanged for 27 mm lock inserts, type A
Base material	Carbon steel
Packaging unit	1 pc(s).
Weight/packaging unit	18.8 kg 41.4 lb.
Copper weight (kg per piece)	0
Customs tariff number	94032080
EAN	4028177923225
ETIM 7.0	EC002504
ECLASS 8.0	27180505

---

# Approvals

# Approvals

---

Approvals

GOST  
UL + C-UL (listed)

---

Explanations

Declaration of conformity  
Declaration of conformity UK